


## DA314-8K2-8K2

**Resistor pack** 

Two resistors pre-wired, as below.



| Connections                               |                                   |        |
|---|-----------------------------------|--------|
| FL1                                       | Fly lead – 📕 green 100mm          |        |
| FL2                                       | Fly lead – blue 100mm             |        |
| FL3                                       | Fly lead – blue 100mm             |        |
| R1  | 8Κ2Ω                              |        |
| R2  | 8Κ2Ω                              |        |
| Environmental                             |                                   |        |
| Operating temperature                     | -10°C to +40°C                    |        |
| Storage temperature                       | -20°C to +50°C                    |        |
| Operating relative humidity               | Maximum 95% non-condensing        |        |
| Dimensions*                               |                                   |        |
| Width                                     | 10mm                              |        |
| Height                                    | 18mm                              |        |
| Depth                                     | 4mm                               |        |
| Weight                                    | < 0.005Kg                         |        |
| Enclosure material                        | Polyolefil heat shrunk insulation |        |
| Finish                                    | Black                             |        |
| Other                                     |                                   |        |
| Estimated mean time before failure (MTBF) | 50,000 hours                      |        |
| CE Approved                               | Yes                               |        |
|   | */+/-                             | - 2mm) |

\*(+/- 2mm)