



4680C

IKALL SIMPLEBUS COLOUR CAMERA



Audio/video unit with terminal block, complete with front-adjustable 1/3" CCD colour camera and LED camera illumination. Digital audio management system with Echo-cancelling, watertight loudspeaker and electret microphone, loudspeaker volume can be adjusted from the front. Complete with microprocessor and DIP switch with 8 positions for programming calls to users. Audiovisual indications to comply with DDA via programming. 33Vdc power supply via power supply unit part. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay and timed lock-release input and door open indication. For use in modules part. 33410, 33411 and 33412. Compatible with all SBTOP functions and products. Dimensions: 102x55x38 mm.



4680C

IKALL SIMPLEBUS COLOUR CAMERA

MAIN FEATURES

Audio/video system:	Yes
Audio/video system:	Yes
Camera:	Colors
Video encoding:	
Type of sensor:	
Horizontal resolution (TVL):	540
Minimum illumination (lux):	0.35
Lens size (inch):	3.60
Camera orientation:	Yes
Clamps:	L L V+V- RTE DO PR GND SE COM NC NO
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
Signal/noise ratio (dB):	48
Video output:	1Vpp 75PAL

SOFTWARE/FIRMWARE SPECIFICATIONS

Video resolution HxV (inch):	500x582
------------------------------	---------

FUNCTIONS

Key button function:	Yes
----------------------	-----

HARDWARE SPECIFICATIONS

Visual signalling:	Yes
Acoustic signalling:	Yes
Speech synthesis:	Yes

SETTINGS

Loudspeaker volume control:	Yes
Microphone volume control:	Yes

GENERAL DATA

Product height (inch):	2.17
Product width (inch):	4.02
Product depth (inch):	1.5

COMPATIBILITY

Simplebus Top audio/video system:	Yes
-----------------------------------	-----



4680C

IKALL SIMPLEBUS COLOUR CAMERA

ELECTRICAL SPECIFICATIONS

Door release (dry contact bridge):	Yes
Door release (direct current output):	Yes