



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM



2-wire Simplebus door entry monitor kit comprised of: 1 Quadra series wall-mounted external unit art. 4893, 1 power supply unit art. 1209, 1 Icona series color monitor art. 6601W, 1 flush-mounted box art. 6117, 1 wall-mounted bracket art. 6620, 1 distribution terminal art. 1214/2C and 1 line closure terminal art. 1216.

AWARDS

DESIGN
MILANODESIGN PLUS
powered by 



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

KIT PRODUCT



6601W

ICONA MONITOR, SBTOP

Flush-mounted (in box Art. 6117) or wall-mounted (with bracket Art. 6620) colour monitor with 4.3" 16/9 screen, Full-Duplex hands-free audio and touch-sensitive controls. Allows adjustment of brightness level, contrast, audio volume and ringtone volume. Ringtones can be customised by selecting from the various melodies provided. Fitted as standard with a key button, enable/disable audio button with corresponding indicator LEDs and a further 7 programmable buttons for self-ignition, privacy service and other programmable functions. It is normally used for floor door call and call repetition management, and comes complete with 2 x 8-position DIP SWITCHES for user code programming and button programming. Equipped with riser distribution terminal Art. 1214/2C. The monitor can only be used in 2-wire SimplebusTop Colour systems. Dimensions 142.5x147x23 mm.

MAIN FEATURES - 6601W

Audio system:	No
Audio/video system:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	Yes
Induction loop function:	No
Type of display:	LCD
Display size (inch):	4,3" 16:9
Touch screen display:	No
Display resolution HxV (mm):	480x272
B/W or colour display:	Color
Product colour:	White RAL9003
Sensitive Touch technology:	Yes
Total buttons:	9
Comaptibility with Video Entry Comelit App:	No



4893M

QUADRA ENTRANCE PANEL W/ BUTTONS. 2 WIRES

Quadra series wall-mounted external video entry unit with mechanical buttons. Die-cast aluminium faceplate, wide-angle colour camera and a single LED for nighttime lighting. Indicator LED for call sent, lock-release activated, audio activated and system busy. Adjustment of speaker volume and audio balance. Power supply from bus line. External unit dimensions: 95x195x28 mm.

MAIN FEATURES - 4893M

Type:	Monoblock entrance panel
Material:	Die-cast aluminium
Audio/video system:	Yes

The technical specifications are subject to variations without warning.



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

MAIN FEATURES - 4893M

Wall-mounted:	Yes
Camera:	Colors
Type of sensor:	1/4" CMOS
Lens size (mm):	2,1
Diagonal viewing angle (°):	100
Minimum colour lighting (lux):	1
Power supply:	Bus
Maximum current absorption (mA):	250
Clamps:	LL RTE COM DO SE- SE+C NC NO
Buttons to call:	Yes
Total buttons:	4
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55
IP protection rating:	IP54
Vandal Resistant rating (IK code):	IK08
Backlighting colour:	White

1216



SIMPLEBUS/KIT SYSTEM TERMINAL

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

6117



FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm

MAIN FEATURES - 6117

Product height (mm):	132
Product width (mm):	132
Product depth (mm):	50



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

KIT PRODUCT



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



1209

2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).

MAIN FEATURES - 1209


Alternating input voltage (VAC):	110÷240
Output voltage (VDC):	33
Input connector:	Terminal block
Applicable to DIN rail:	Yes
Number of DIN modules:	6
Max. current delivered (A):	1,20



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM


ACCESSORIES



4791

Adapter plate for Quadra

Plate allowing installation of the Quadra external unit in 1- and 2-module flush-mounted boxes by Comelit, Bticino and Urmet. Dimensions 137x236 mm



4792

RAIN SHIELD FOR QUADRA ENTRANCE PANEL

Rain shield in painted aluminum for Quadra entrance panel, grey colour. Dimensions (W x H x D): 99 x 210 x 41 mm.



4793MB

BLACK FACEPLATE FOR QUADRA W/BUTTONS



4793MC


CORTEN FACEPLATE FOR QUADRA W/BUTTONS

Corten color faceplate for Quadra entrance panel with mechanical buttons.



4793MA

ALUMINIUM FACEPLATE FOR QUADRA W/BUTTONS



1217

NAME TAG SHEETS FOR QUADRA ENTRANCE PANEL

The kit contains 10 sheets of adhesive labels for nameplates



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

ACCESSORIES



1235A

NAMEPLATE LABEL PRINTING SOFTWARE

Dedicated software for the creation and printing of nameplate and information labels for Ikall, Vandalcom, Quadra and 316 Analog entrance panels. Requires use of adhesive labels art.1217, 1218, 1219 or art.1220. This software is available to download free of charge from the Comelit website



6117

FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm



6118

PLANUX CLIPS FOR DRY LINED WALLS

Installation kit for plasterboard walls.



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 137X142X12.5 mm.



6612

DESK BASE FOR ICONA MONITOR

Adjustable tilt desk base converts the Smart monitor into a desktop version. Complete with 1 x 2 m labelled RJ45 cable for connecting the monitor terminals to the clasp or to a residential series jack. Dimensions: 145x190x120 mm.



1209

2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).



84611

SINGLE-FAMILY KIT WITH QUADRA AND ICONA. SB SYSTEM

ACCESSORIES



1229A

ADDITIONAL RINGTONE ACCESSORY FOR SIMPLEBUS2 SYSTEM

Wall-mounted accessory for additional ringtone for direct connection to 2-wire bus. Allows ringtone selection and adjustment of ringtone volume with privacy function, equipped with dip switches for user code programming, floor door call input terminals and call repeat. Fitted with distribution terminal art. 1214/2C. Dimensions: 125x95x24mm.



1256

ACCESSORY - SIMPLEBUS SYSTEM DIGITAL RELAY ACTUATOR

Intelligent Simplebus device for controlling a 10 A (12-24 V relay contact) on board. It can be used in Simplebus 1 and Simplebus 2 systems. For use and programming of the function required, follow the indications given in the technical documentation. If used in mixed audio/video systems, the actuator relay needs terminal art. 1214/2 to be purchased separately. Power supply: 12V AC or 20V DC. Dimensions: 66X85X35 (4 DIN modules).



1404

DIGITAL SWITCHING DEVICE. 2-WIRE SYSTEM

Audio/video switching module for Simplebus Top 2-wire digital systems. To be used in systems with more than one entrance. Power supply from bus line. Dimensions: 60x85x35 mm (4 DIN modules).



1405

DIGITAL EXCHANGE 2 QUADRA INPUTS. SBTOP

Audio/video switching module for audio/video kit systems. For use in systems with a maximum of 2 entrances with Quadra series external unit. Power supply from bus line. Dimensions: 35x90x58mm (2 DIN modules).



1409

ACCESSORIO PER TELECAMERE SCORPORATE A COLORI.SIST

Remote camera module for Simplebus Top 2-wire digital systems. Allows management of up to 3 colour cameras in cyclical sequence from door entry monitors using a dedicated button. 12 Vac or 20 Vdc power supply. Dimensions: 60x85x35 mm (4 DIN modules).