

17" Security TFT



Specifications

LCD	17" TFT LCD	Response	8ms
Display Size	337.9(H) x 207.3(V) mm	Signal Connector	VGA: 1PCS
Pixel Pitch	0.264(H) x 0.264(V) mm		BNC: 2PCS
Display Mode (VGA)	VGA 720 x 400 (70 Hz)	OSD	AUDIO: 2PCS
	VGA 640 x 480 (60/72/75 Hz)	Plug & Play	Colour, Adjust, OSD, Function and Sound
	SVGA 800 x 600 (60/72/75Hz)	Audio System	DDC1 / 2B
	XGA 1024 x 768 (60/72/75Hz)	Power Adapter	1W / Per channel
	SXGA 1280 x 1024 (60/72/75Hz)	Operating Conditions	Input AC 100-240V, 50-60Hz,
Max. Resolution	SXGA 1280 x 1024	Storage Conditions	Output DC 12V/4A
Display Color	16M	Size (LxWxH)	Temperature: 5°C ~ 35°C
Contrast Rate	700: 1	Net weight	Humidity: 20% ~ 80%
Brightness	300 Cd/ m2		Temperature: -20°C ~ 60°C
Viewing Angle (CR≥10)	H: +75 ~ -60° (U/D)		Humidity 10% ~ 90%
	V: +75 ~ 75° (L/R)		
Input Signal	VGA: RGB Analog 0.7V		
	VIDEO: PAL/NTSC		