

**SITA
FLASHPOINT**

The Sita Flashpoint allows a simple and effective visual indication directly from the loop wiring, complete with a sounder.

It has been designed to comply with the European standard EN54 part 3.

This loop powered combined sounder and beacon is available in a low profile or domed version, and can be manufactured in alternative colours if required.

Whilst in alarm the flashpoint synchronisation is uniquely reset every 10 seconds to ensure that the beacon's flash rate remains in absolute synchronicity across the entire system.

Installation is simple by first fixing the base and then simply plugging in the unit.

As with all Rafiki sounders the flashpoint features an anti-tamper mechanism to ensure that the device is only released with the use of the head removal tool.



Technical specifications		
Compatibility:	Sita 200 plus	
Operating Temperature:	-10°C to 50°C	
Voltage Range:	16 to 48v DC	
Operating Current:	Quiescent:	93uA
	MCP alarm:	4mA
	Sound low:	1.5mA
	Sound med:	4mA
Loading:	Sounder low:	0.5 ALU
	Sounder med:	1 ALU
	Sounder hi:	2 ALU
	Beacon 15ms/1ms:	1 ALU
Sound Outputs:	Low:	75dB(A)
	Mid:	85dB(A)
	High:	95dB(A)
LED Operation:	Quiescent:	20s interval
Part Code:	Low Profile:	303 0012
	Domed:	303 0022

