



Securit 800L

Eight Zone Control Panel

Simple to operate
residential/light
commercial alarm
control panel



Features

- **Versatile Installation**
Designed with both the user and installer in mind, the Securit 800L's main control unit can be mounted quickly and easily both out of sight and out of mind.
- **User-Friendly Design**
For people who have difficulty in using a keypad, C&K have included a keyswitch option which is designed to make usage simpler.
- **Easy to Operate Remote Keypad**
Slim, compact keypad which unobtrusively blends into its environment. With audible key-press confirmation on the backlit tactile keys. The on-board Day LED allows the user to constantly monitor the system's status.

Features

Eight Zones (Alarm)

6 Programmable for: Alarm, Entry/Exit, Access (walk through), Personal Attack, Part Set Entry, Part Set Isolation.

1 Programmable for: Entry, Alarm, Fire, Keyswitch.

1 Fixed: Entry/Exit.

Door Sense Setting

Allows easy setting of the system without having to wait for the exit timer to Run out.

Home Set Facility

Gives flexibility by automatically isolating pre-programmed zones, allowing the system to be armed while the User remains inside.

Manual Isolation

The system can be tailored for any situation that arises by isolating individual zones which have not been programmed for Home or Part Set Isolation.

Remote P.A. Option

The Remote keypads can be programmed to give a Personal Attack Feature, using the * and # Keys.

Extension Speaker Output

For greater enhanced sounds, up to two 16 Ohm extension speakers can be fitted.

Chime Function

Enabling this feature allows Monitoring of chosen zones while the panel is disarmed.

Two User Codes

Main User code plus second code for children or cleaner etc.

Specifications

Securit 800L Control Panel

Dimensions

Height : 261 mm

Width : 266 mm

Depth : 88 mm

Material : white, epoxy powder coated, 18 swg shell

Weight : 3.10 kg

Mains Supply Voltage

230 V AC Nominal.

PSU Output Voltage

13.6 V Nominal.

Maximum Output Current

1 A (total).

Event Memory

Allows checking of past events.

Panel Quiescent

40 mA.

Normal Operating Temperature

0°C to 40°C.

Humidity

10 to 90% R.H. non-condensing.



Keypad

Dimensions

Height : 70 mm

Width : 120 mm

Depth : 25 mm

Weight : 0.13 kg

Supply Voltage

12 V.

Quiescent Current

20 mA.

Active

45 mA

Maximum Number Allowed

Six.

Approvals

CE Designed to comply with BS4737 Part I, and BSEN50131-1 (Grades 1&2).

Ordering Part Number

ST 800L.



For further information, please contact:

