

IntelliSense 800L

The Complete Professional Package



FEATURES

- Combines proven technology
- Attractive styling
- Easy to operate functions
- Complete Professional Pack
- Reliable and flexible system

PACK INCLUDES

- ST800L simple to operate 8 zone control panel, including one compact LED keypad
- AG3 or AG6 state-of-the art high powered polycarbonate sounder
- AG3 or AG6 dummy sounder
- Four IS-215T 12m x 12m passive infra red sensors, including look-down zones
- 12V/2Ah rechargeable Yuasa battery
- Two EMPS85W surface mount contacts
- 100 Metres of 6 core cable
- Spur and Pattress
- Full easy to follow step by step instructions

IntelliSense 800L

The Complete Professional Package

SPECIFICATIONS

Securit 800L simple to operate 8 zone control panel:

- Eight hardwired zones plus tamper zone of which 7 zones are programmable.
- The Securit 800L's main control unit can be mounted quickly and easily both out of sight and out of mind.
- It includes one compact LED keypad and incorporates the ability to add up to six remote LED keypads in case additional setting points are required.
- Full set, night set and home set options provided to simplify operation and match user operational needs.

Securit 800L user-friendly LED keypad:

- Slim, compact keypad which unobtrusively blends into its environment
- Audible key-press confirmation on the back-lit tactile keys.
- The on-board day LED allows the user to constantly monitor the system's status

AG3 External Sounder:

The ActiveGuard AG3 external sounder is designed to be simple to install and offers a wide variety of features and safeguards.

Current	Single Piezo	125 mA (160mA Max.)
Sound Pressure	Single Piezo	114 dBA@ 1M (116 dBA Peak@ 1M)
Trigger	Un-Monitored	Negative Applied
Trigger	A	20 minutes Nominal
T	5 Seconds Nominal	

AG6 External Sounder:

The ActiveGuard AG6 external sounder is designed to be simple to install with keyhole fixings and offers a wide variety of features and safeguards.

Current	Single Piezo and strobe	350 mA
Sound Pressure	Single Piezo	110 dB@ 1M norm (supply and mounting dependent)
Trigger	Un-Monitored	Negative Applied
Trigger	A	15 minutes Nominal

IS-215T passive infra red sensor:

The IS-215T motion sensor offers quality detection and simple installation, designed for residential and light commercial applications.

- 12m x 12m detection pattern
- Attractive, sleek design
- Look-down zones
- Mounting flexibility
- Sabotage-resistant lens design
- Selectable sensitivity
- Tamper switch
- White light immunity
- Bug guard

Battery:

12 Volt – 2 Ah rechargeable Yuasa battery

EMPS 85W Magnetic Contact:

A surface mount magnetic contact with 5 screw terminals.

Dimensions switch:	64 x 14 x 12 mm (HxWxD)
Dimensions magnet:	64 x 14 x 12 mm (HxWxD)
Gap distance:	20 mm

Other:

100 meters of 6 core cable, Spur and pattress

Easily Expandable with Optional Products:

Up to 6 remote keypads. Additional passive infra red sensors, Dual Tec sensors, contacts, breakglass sensors

ORDERING