

High Resolution Mono & Colour Vandal Resistant Dome Cameras



Features

- ✓ Tamper and vandal resistant aluminium housing
- ✓ Impact resistant clear 75mm polycarbonate bubble
- ✓ Integrated fixed lens options
- ✓ Surface and flush mount options
- ✓ Standard resolution
- ✓ Impressive colour reproduction
- ✓ Backlight compensation
- ✓ Automatic Gain control
- ✓ Line lock with phase adjustment
- ✓ Unique 3 axis gimble
- ✓ Weatherproof (IP66 rated)

Optional Accessories:

AVRWB Wall mount bracket (comes with a fixing kit)

Technical Specification

Model No.	AVR35M	AVR35MX	AVR35C
Type	Mono	Mono	Colour
Image Sensor	1/3" IT CCD	1/4" EXVIEW CCD	1/3" IT CCD
Video Format	PAL		
Horizontal Resolution	600 TVL	600 TVL	480 TVL
Scanning System	2:1 Interlace		
Effective Pixels (H x V)	752 x 582		
Lens	3.6mm	3.6mm	4.0mm
Minimum Illumination	0.1 Lux @ F1.2	0.001 Lux @ F2.0	0.7 Lux @ F1.2
Synchronisation	Internal line lock		
Video Output	1.0 V(p-p) / 75 ohm, Unbalanced		
Electronic shutter	1/50 – 1/100,000 seconds		
Automatic Gain Control	Yes		
White Balance	AWB		
S/N Ratio	>48dB		
Power consumption	100mA	110mA	160mA
Power Supply	12V DC		
Operating Temperature	-10°C ~ +50°C		
Operating Humidity	10%~90% RH		
Dimensions (D x H)	Ø129 x 104 mm		
Weight	944g		

Features and specifications are subject to change for further improvement without any notice