

High Resolution Mono & Colour Vandal Resistant Dome Cameras



Features

- ✓ Tamper and vandal resistant aluminium housing
- ✓ Impact resistant clear 75mm polycarbonate bubble
- ✓ Integrated Varifocal lens options
- ✓ Surface and flush mount options
- ✓ High resolution
- ✓ Impressive colour reproduction
- ✓ Backlight compensation
- ✓ Automatic Gain control
- ✓ Line lock with phase adjustment
- ✓ Unique 3 axis gimble
- ✓ Weatherproof (IP66 rated)

Optional Accessories:

AVRWB Wall mount bracket (comes with a fixing kit)

Technical Specification

Model No.	AVR35MV	AVR35MVAI	AVR35MXVAI	AVR35CV	AVR35CVAI
Type	Mono	Mono	Mono	Colour	Colour
Image Sensor	1/3" IT CCD				
Video Format	PAL				
Horizontal Resolution	600 TVL			480 TVL	
Scanning System	2:1 Interlace				
Effective Pixels (H x V)	752 x 582				
Lens	4.0 – 8.0mm	3.8 – 9.5mm	3.8 – 9.5mm	4.0 – 8.0mm	3.8 - 9.5mm
Minimum Illumination	0.1 Lux@F1.2	0.1 Lux@F1.2	0.001 Lux@F1.2	0.7 Lux@F1.2	0.7 Lux@F1.2
Synchronisation	Internal line lock				
Video Output	1.0 V(p-p) / 75 ohm, Unbalanced				
Electronic shutter	1/50 – 1/100,000 seconds				
Automatic Gain Control	Yes			Yes, selectable	
White Balance	AWB				
S/N Ratio	>48dB				
Power consumption	100mA	150mA	150mA	160mA	180mA
Power Supply	12V DC				
Operating Temperature	-10°C ~ +50°C				
Operating Humidity	10%~90% RH				
Dimensions (D x H)	Ø129 x 104 mm				
Weight	944g				

Features and specifications are subject to change for further improvement without any notice

Genie CCTV Ltd.

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT
 tel: +44(0) 1707 330541 fax: +44(0) 1707 330543
 website: www.geniecctv.com email: info@geniecctv.com