

TECHNICAL DATA SHEET

AVRCD-5351

Day/Night Vandal Dome With 2.9-10mm VF AI Lens, 12V



KEY FEATURES

- 1/3" Sony Super HAD CCD
- Super High Resolution, 540 TVL
- Tamper & Vandal Resistant Housing
- Digital Day / Night
- Dual Mount (Surface / Flush Mount)
- Digital Noise Reduction (DNR) - 4 Levels
- Saves Up To 70% HDD Storage with DNR, Using MPEG 4 Codec
- Automatic Gain Control
- Back Light Compensation
- O.S.D. Menu
- Mirror Function
- Privacy Masking
- Motion Detection
- Weatherproof (IP66 Rated)
- Three Axis Gimbal
- DC 12V

OPTIONAL ACCESSORIES

CCTV Power Supply In-Line 12V DC 1A Regulated Switch Mode Power Supply Unit with Fixing Mount.

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	AVRCD-5351
Image Sensor	1/3" Sony Super HAD CCD
Horizontal Resolution	540 TVL (Col) 570 TVL (Mono)
Sensitivity (50 IRE @ F1.2)	0.3 Lux (Col) 0.1 Lux (Mono) 0.002 (Using Sens-Up)
Lens	2.9-10mm
Effective Pixels (H x V)	752 x 582
Electronic Shutter Speed	Auto/Manual 1/50 ~ 1/120,000 Seconds
Scanning System	2:1 Interlace
Synchronisation	INT/LL Selectable 0~359° (Adjustable)
Frequency	Horizontal: 15.625KHz Vertical: 50Hz
Video Output	1.0Vp-p~75 Ohm
S/N Ratio	>50dB (AGC Off)
VBS Extra Connector	For Local Connection of Test Monitor
Colour	ON / AUTO
DNR	OFF / LOW / MIDDLE / HIGH
O.S.D.	Yes Built-In
Gain Control	OFF / LOW / MIDDLE / HIGH
White Balance	ATW / AWC / MANUAL
Back Light Compensation	OFF / LOW / MIDDLE / HIGH
Mirror	Built In
Sens-Up	OFF / AUTO
Privacy Function	ON / OFF (4 Programmable Zones)
IP Rating	IP66
Operating Conditions	Temperature: -10°C ~ +50°C Humidity: 30 ~ 90% RH
Power Supply	DC 12V
Power Consumption	12VDC (Max 160mA)
Dimensions (D x H)	143.64 x 119 mm
Weight	1100g

Features and specification are subject to change for further improvement without any notice.