



REMOTELY ACCESSIBLE VIA INTERNET & MOBILE PHONE

Supports iPhone, Android, Windows Mobile & Blackberry.

Blackberry and Android software Included, iPhone software "MEye" available free from App store.

* Mobile Devices Not Included.

1TB H.264 Networked DVR

Image Compression System	H.264 NTSC/PAL
Video Input	4 Channels 1.0Vp-p, 75 Ω BNC
Video Output	1 Channels 1.0Vp-p, 75 Ω BNC
Audio Input	2 Channels 1.0Vp-p, Impedance 600 Ω RCA
Audio Output	1 Channels 1.0Vp-p, 600 Ω RCA
Audio Compression	ADPCM
Recording Frame Rate	PAL: 100 fps, NTSC: 120fps
Recording Resolution	PAL: CIF352 x 288 Pixels, NTSC: CIF352 x 240 Pixels PAL: D1 720 x 576 pixels, Single picture or quad display
Display resolution	PAL: D1, HD1, CIF
Video Playback	Supports 4 channels playback at the same time
HDD	1TB SATA
USB Interface	1 USB2.0 Port For Backup; 1 USB 1.1 for mouse
Motion Detection	Zone setup: PAL13 x 10 (130) NTSC13 x 8 (104)
Network Interface	RJ-45, 10M/100M
Power Source	DC 12V/3A
Mobile Monitoring	Support GPRS/CDMA/EDGE/3G
VGA Interface	Yes
Operating Temperature	0~50°C
Dimensions	300mm x 250mm x 60mm

19" Monitor

Display Size	19"
Pixel Pitch	0.294mm
Max. Resolution	1280 x 1024
Refresh Rate	75hz
Contrast Ratio	2000:1
Brightness	300cd/m2
Viewing Angle	1600 (H), 1600 (V)
Colours	16.7 million
Power Supply	100-240 v 50/60Hz 1.1A

Whats in the Box

19" Monitor	VGA to monitor Cable
1TB H.264 Network DVR	Power adapter
2 x Sony CCD IR Outdoor Bullet Cameras	5 to 1 power splitter cable
2 x Sony CCD IR Outdoor Vandleproof Dome Cameras	USB Mouse
2 x Mounting brackets	Remote Control
4 x 18.3m camera cables	Instruction manual

x2 Sony CCD Bullet Cameras

Sensor type:	1/4 SONY CCD
Sensor size:	1/4"
Viewing angle:	75°
Lens focal length:	3.6mm
Electronic shutter:	1/50 (1/60) — 1/100,000 (s)
TV system:	PAL
Effective Pixels:	PAL:500(H)×582(V) NTSC:510(H)×492(V)
Resolution:	420TV Line
Video output:	1.0Vp-p,75 Ω (BNC)
Number of LEDs:	12
Night vision range:	10-15m
Minimum illumination:	0LUX
Signal noise ratio:	More than 48db (AGC OFF)
Audio:	No
Power supply:	DC12V
Gain control:	Auto
IP rating:	65
Video connections:	BNC connector
Wireless:	No
Operating temperature:	-10°~+50°

x2 Sony CCD Dome Cameras

Sensor type:	1/4" Sony CCD
Sensor size:	1/4"
Viewing angle:	62°
Lens focal length:	3.6mm
Electronic shutter:	1/50 (1/60) — 1/100,000 (s)
TV system:	PAL
Effective Pixels:	PAL:500(H)×582(V) ; NTSC:510(H)×492(V)
Resolution:	420TV Line
Video output:	1.0Vp-p,75Ω (BNC)
Number of LEDs:	12
Night vision range:	10-15m
Minimum illumination:	0.05Lux/F1.2
Signal noise ratio:	More than 48db
Audio:	No
Power supply:	DC 9-14V
Gain control:	Auto
IP rating:	65
Video connections:	BNC connector
Wireless:	No
Operating temperature:	-10°~+50°
Vandalproof:	Yes