

FG-1615

The new FG-1615 Glassbreak Detector uses the latest technology to provide faster response and increased false alarm immunity. The FG-1615 is designed to allow fast and easy installation. Optimum operation can be quickly verified using the FG-701 Glassbreak Simulator.

FEATURES:

FlexCore™ Signal Processor

The FlexCore Signal Processor is an Application-Specific Integrated Circuit (ASIC), which processes sound data in parallel rather than sequentially; for faster, more accurate detection decisions.

The combination of proven FlexGuard® performance with the speed of FlexCore processing provides unmatched false alarm immunity without compromising detection.

Easy Installation and Setup

IntelliSense's patented technology allows remote activation of Test Mode (w/simulator). The FG-1615 has a centered wire entry hole, 45° terminal blocks, and EOL terminals. A hand-clap feature verifies that the detector is functioning. No sensitivity adjustments are required.

Mount the Detector Anywhere

Mounts on any wall, in the window frame, or on the ceiling, with no minimum range and a maximum range of 15' (4.6 m) to the glass.

Covers All Glass Types

The FG-1615 works on all glass types, including plate, tempered, laminated, wired, film-coated, and sealed insulating glass.

Multiple Domain Signal Analysis

The FG-1615 performs Multiple Domain Signal Analysis in which time, frequency and amplitude characteristics are evaluated for signal qualification. This enables the detector to accurately distinguish false alarms from true glassbreak events.

Remote Test Mode Enable/Disable

The Patented Remote Test Mode can be enable or disable the indicator LEDs remotely using the FG-701 Glassbreak Simulator. The unit automatically resets from Test Mode in five minutes.

Enclosed PC Board

The PCB is protected from potential damage during installation.



**Glassbreak
Detector**

IntelliSense

FG-1615

SPECIFICATIONS:

Physical Dimensions:

3 7/8" x 2 2/5" x 7/8"

(98 mm x 62 mm x 21.8 mm)

White high impact ABS plastic housing

Weight:

Product only 3.2 oz. (90 g)

Pkgd. Product 4.1 oz. (116 g)

Range:

15' (4.6 m) maximum, omnidirectional
no minimum range

Alarm Relay:

FG-1615 Form A, 125 mA max. 25 VDC max.

FG-1615T Form C, 125 mA max. 25 VDC max.

Alarm Duration:

Five seconds (unaffected by alarm
LED latching)

ESD Immunity:

10kV discharges of either polarity to
exposed surfaces

Power Requirements:

6 to 18VDC; 12mA typical at 12VDC, 22mA
max, (Latched LED) AC ripple: 4V peak-to-
peak at Nominal 12VDC

RFI Immunity:

30V/m, 10MHz to 1000MHz

Operating Temperature:

14° to 122° F (-10° to 50° C)

Storage: -4° to 122° F (-20° to 50° C)

Tamper (FG-1615T only):

Combination cover/wall tamper
25mA max., 24VDC max.

Approvals and Listings:

FCC and IC Verified

UL Listed

ULC Listed

CE



ORDERING:

Part No.

FG-1615

FG-1615T

Description

Glassbreak Detector

Glassbreak Detector with Tamper

Glass Type/Thickness

Type*	Minimum	Maximum
Plate ^{3a}	2.4 mm (3/32")	10 mm (3/8")
Tempered	3 mm (1/8")	10 mm (3/8")
Laminated ¹	3 mm (1/8")	14 mm (9/16")
Wired	6 mm (1/4")	6 mm (1/4")
Coated ^{2,3b}	3 mm (1/8")	6 mm (1/4")
Sealed	3 mm (1/8")	6 mm (1/4")
Insulating ^{1,3b}	(Maximum overall 7/16")	

¹ Protected only if both plates of the unit are broken.

² Coated glass with security films, including films for solar protection, up to 12 mil. thick may be used. Film Technologies International, Inc.'s GLASS-GARD® GGLL 1200 has been evaluated with this product by Underwriters Laboratories, Inc. at the request of IntelliSense.

³ In compliance with Underwriters Laboratories of Canada's Standard for Intrusion Detection Units (CAN/ULC-S306-M89):

a. Plate glass 3mm to 10mm can be used.

b. ULC recognizes a maximum range for protecting sealed insulated glass and coated glass of 7.5 ft. (2.3 m).

Note: The FG-1615/1615T detects shattering of framed glass by direct impact. It may not consistently detect breakage by blows that only crack the glass, by high velocity projectiles such as bullets, or glass broken without an impact.

Accessories

Description

FG-701 P/N 0-000-701-01 Glassbreak Simulator

FlexGuard® Glassbreak Simulator/Tester

The sound of breaking glass is digitally simulated by the FG-701. The FG-701 is compatible for testing all IntelliSense glassbreak detectors. IntelliSense highly recommends testing glassbreak detectors before final installation. (See the FG-701 Operating Instructions).

© 2002 IntelliSense® • IntelliSense and FlexGuard are registered trademarks of Honeywell, Inc. • All other trademarks are the properties of their respective owners. • All rights reserved.

**Glassbreak
Detector**

1230 S. Hurstbourne Pkwy.

Suite 100

Louisville, KY 40222

1-800-467-5875

IntelliSense