

DIGIVIEW⁴PRO

4 channel Day/Night CCTV system with integral 160GB hard drive



Now with
REMOTE CONTROL



RECORDING OPTIONS



- Day/night cameras with LED illumination
- Picture in picture viewing
- Improved search and review facility
- Simple backup to USB memory stick
- Complete with Seagate SV35 hard drive
- USB output for easy PC linkage with new enhanced software
- Integral power for 12Vdc cameras up to 2000ma (500ma/channel)
- Built in 'on-screen' motion detection no PIR required
- Up to 7 months continuous recording
- Networkable version Digiview 4 PRON available with enhanced remote viewing software
- Compatible with XP and Vista
- Slow motion facility in forward and reverse
- Individual channel set up

CAMERAS



Colour during daylight



Black & white at night

DISPLAY OPTIONS



PIP (Picture in picture)



Auto Sequence



Quad Screen



Single Screen



www.espuke.com

DIGIVIEW 4 PRO

4 channel Day/Night CCTV system with integral 160GB hard drive

Digiview 4 Pro offers a comprehensive digital CCTV solution for home or business use. The cameras, suitable for exterior or interior use without any additional housing, offer clear colour images during the day and crisp infra red illuminated mono images at night. Also included in the system is a high capacity digital video recorder which allows simple control, recording and viewing of images whilst also providing power for the cameras. To complete the system a cable is included for direct connection to a standard television or an optional dedicated CCTV TFT monitor.

Digiview 4 Pro offers the user many recording options in order to optimise the 160Gb of record space available, there is even built in motion detection which looks for movement on screen, without need for additional equipment, to trigger a record session.

Back-up
to USB via
memory stick



DVR SPECIFICATION		CAMERA SPECIFICATION	
Product code	DIGIVIEW 4 PRO & DIGIVIEW 4 PRON	Description	1/4" Colour Day & Night Infrared Camera
Description	4 channel stand alone DVR	Pick up Element	SHARP 1/4" CCD Image Sensor
Hard drive	Removeable 160GB Seagate SV35	Number of Pixels	NTSC 510(H) x 492(V), PAL 500(H) x 582(V)
Max HDD supported	750GB in single bay	Back Light Compensation	ON
Video input format	PAL/NTSC	Auto Electronics Shutter	ON
Video input	4 channel composite	AGC	ON
Video output	4 channel composite	Sync Mode	Internal Sync
Power output	500ma 12VDC each channel	Scanning System	2:1 Interlace
Motion detection	Area selectable - Sensitivity adjustable	Auto White Balance	ON
Alarm input	4 selectable no/nc	Resolution	420 TV Lines
Alarm outputs	1 selectable	S/N Ratio	> 48 dB
Alarm buzzer	Yes	Gamma	0.45
Display frame rate	100 frames per second	Minimum illumination	0.92 Lux. F /2.0 (0 Lux with IR)
Record frame rate	Max 25 frames per second adjustable	Horizontal Sync Frequency	<PAL> 28.3 KHz
Record quality	Adjustable - Super , High , Normal , Standard	Video Output	1.0Vp.p. 75ohm
Recording modes	Continuous, motion, manual, scheduled	Power Source	DC 12V (Supplied from DVR)
Display resolution	720 x 576	Water Resistance	IP66
Recording resolution	704 x 576	IR LED	10PCS
Compression format	Selectable MJPEG or MPEG4	Night Viewable Range	5-8 meters
Search facility	Time/Date or Event	Power Consumption	350mA max
Recorded image back up	USB flash stick or direct to PC/Laptop	Operating Temperature	-10°C to + 60°C
		Lens	4mm lens
		Shutter Control	<PAL> 1/50-1/110,000 sec
		Dimension	52 (D) x 75 (H) mm
		Net Weight	0.6kg

RECORDING DURATION							
MJPEG Compression				MJPEG4 Compression (Dual Codec Mode Only)			
SUPER FPS	HOURS	HIGH FPS	HOURS	NORMAL FPS	HOURS	STANDARD FPS	HOURS
1	2,167	1	2,543	1	2,988	1	3,528
2	1,084	2	1,271	2	1,494	2	1,764
4	542	4	636	4	747	4	882
8	271	8	318	8	374	8	441
15	144	15	170	15	199	15	235
30	72	30	85	30	100	30	118
2	3,251	2	3,814	2	4,482	2	5,292
4	1,625	4	1,907	4	2,241	4	2,646
8	813	8	953	8	1,121	8	1,323
15	433	15	509	15	598	15	706
30	217	30	254	30	299	30	353
60	108	60	127	60	149	60	176



ESP - Electronics Line UK Ltd

Unit 7, Levis Trading Estate, Station Road, Stechford, Birmingham B33 9AE
Tel: (+44-121) 789 8111 Fax: (+44-121) 789 8055 info@espuk.com

www.espuk.com