


The monitors from the TK Series feature a metal housing with a tempered glass protected panel for added durability. They deliver crisp clear images and offer BNC, VGA and S-Video connections making them the ideal solution for a wide variety of CCTV monitoring applications.



LCD-150TK



Features

- 15" LCD monitor
- 1024 (H) x 768 (V) resolution
- Metal case with tempered glass protected panel
- Brightness 250cd/m²
- 500:1 contrast ratio
- 12 ms response time
- Power input: 230VAC
- 1x VGA, 1x BNC (In and Out), 1x audio, 1x S-Video
- VESA 100
- Remote control included

General Specifications

Panel Type	15" TFT active matrix
Pixel Pitch	.297mm (H) x.297mm (V)
Max Resolution	1024 x 768
Aspect Ratio	4:3
Brightness	250cd/m ²
Contrast Ratio	500:1
Viewing Angle	170° (H) / 170° (V)
Display Colours	16.2 Million
Response Time	12ms
Inputs	1x VGA 1x BNC (In and Out) 1x audio (In and Out) 1x S-Video
External Power Adaptor	100VAC/240VAC 50~60Hz
Power Consumption	36W Max
OSD Menu	Yes (English)
OSD Control	Colour, image setting, position, OSD, Misc
Remote Control	Yes
VESA Mount	VESA 100
Dimensions	365mm W x 290mm H x 46mm D
Weight	3.5 kgs