



wLSN Key Fob



The wLSN Key Fob allows remote arming and disarming of a secure area. This key fob has two additional buttons that can be programmed to allow the user to control lights or garage doors and to provide a duress signal. Two status LEDs (one red, one green) indicate status and a high-intensity blue LED operates as a directional close-contact flashlight.

Certifications and Approvals

Listings and Approvals: **CE**
 Complies with: EN50131-1 Grade 2, Environmental class II

Installation/Configuration Notes

Compatibility Information

The wireless Local SecurityNetwork (wLSN) including the wLSN Key Fob is compatible with the Easy Series Control Panel.

- ▶ Small ergonomic design with protected, recessed buttons
- ▶ Energy saving power-down mode until a button is pressed
- ▶ Two programmable buttons can be used for lights, garage doors, or duress
- ▶ Two LEDs (one red, one green) for status; another (high-intensity blue) LED for use as a flashlight
- ▶ Supervised for low-battery condition
- ▶ Personalize the Key Fob with a choice of gasket color
- ▶ Operates for up to 5 years on readily-obtainable lithium button-cell batteries

Parts Included

Quant.	Component
1	Key fob assembled with red gasket
4	Rubber gaskets (black, green, orange, yellow)
2	Lithium batteries (P/N: 34522)
1	Literature pack

Technical Specifications

Environmental Considerations

Environment:	Intended to be connected to key rings, water resistant
EN50131-1:	Environmental Class II
Relative Humidity:	Up to 95%, non-condensing
Temperature (operating):	-10°C to +55°C (+14°F to +131°F)

Mechanical Properties

Color:	Charcoal-gray
Dimensions (H x W x D):	7.4 cm x 3.3 cm x 1.5 cm (2.9 in. x 1.3 in. x 0.58 in.)

Power Requirements

Battery Power

Battery Life:	Up to 5 years under normal operating conditions.
Battery Requirements:	Two lithium button-cell batteries
Recommended Replacements:	Duracell® DL2032, Eveready® ECR2032, Maxell™ CR2032, Panasonic® CR2032, Rayovac® KECR2032, SANYO® CR2032, Toshiba CR2032, VARTA CR2032
Voltage (supply):	2.3 VDC to 3.0 VDC

Transmission and Reception Characteristics

Frequency:	European Security Band 868 MHz to 869 MHz
Range (open field):	1000 m (3000 ft)

Trademarks

Duracell® is a registered trademark of the Gillette Company, USA, in the United States and/or other countries.

Eveready® is a registered trademark of Eveready Battery Company, Inc.

Maxell™ is a trademark of Maxell Corporation of America (MCA), Inc., a wholly owned subsidiary of Hitachi Maxell, Ltd. (Hitachi Maxell), based in Osaka, Japan.

Panasonic® is a registered trademark of a Matsushita Electric Industrial Co., Ltd.

Rayovac® and VARTA are marks of Spectrum Brands, its subsidiaries, and/or its affiliates.

SANYO® is a registered trademark of SANYO North America Corporation.

Toshiba refers to Toshiba America, Inc. (TAI), a subsidiary of Toshiba Corporation based in Tokyo, Japan.

VARTA refers to VARTA Consumer Batteries GmbH & Co., a member of the Spectrum Brands family.

Ordering Information

wLSN Key Fob

ISW-BKF1-H5X

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5600 JB Eindhoven, The Netherlands
Phone: +31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Americas:

Bosch Security Systems, Inc.
130 Perinton Parkway
Fairport, New York, 14450, USA
Phone: +1 800 289 0096
Fax: +1 585 223 9180
security.sales@us.bosch.com
www.boschsecurity.us

Asia-Pacific:

Bosch Security Systems Pte Ltd
38C Jalan Pemimpin
Singapore 577180
Phone: +65 6319 3450
Fax: +65 6319 3499
apr.securitysystems@bosch.com
www.boschsecurity.com

Represented by