

Professional CCTV Portable Tester



- ✓ Compact Hand Held Battery Powered Tester
- ✓ Field Service Monitor with Integral 2.5" TFT LCD Colour Screen
- ✓ Video Signal Generator – Test Bar or Red, Blue & Green Screens
- ✓ PTZ Controller – Fully Controls Speed Dome Cameras with Variable Baud Rates
- ✓ PTZ Protocol Analyser – Displays Hexadecimal Command Code on Tx Data
- ✓ Digital Multimeter – Measures Voltage, Current and Resistance
- ✓ UTP Cable Tester – Tests for Continuity, Shorts, Polarity & Mis-Wires
- ✓ Supplied with Carry Case, Rechargeable Batteries, Charger & Test Leads

technical data

Electronic	Input Voltage	12V ± 10%, 1A or more	
	Battery	Rechargeable Ni-MH (2400mA)	
	Internal Re-Charger	Charge Time	6 Hours (min)
		Operating Time	4 Hours (max)
Video	Video Signal Format	PAL/NTSC – Auto-Sensing	
	Video Out	1.0V p~p	
PTZ Control	Protocol	Multi-Protocol (Inc. Pelco D & P)	
	Baud Rate	2400bps – 38400bps	
	Data Communication	RS422/RS485	
UTP Cable Tester	Tests	Continuity, Crossover, Split Pairs, Shorts and Mis-Wires	
Multimeter	AC-DC Voltage	400V Maximum	
	AC-DC Current	10A Maximum	
	Resistance	40MΩ	
	Continuity	Beeper sounds when a short (less than 80Ω) is detected	
Internal Fuse	250V, 800mA		
Dimensions	190mm (high) x 88mm (wide) x 58mm (deep)		
Weight	390g		