

5.6" LCD Test Monitor

with Test Pattern Generator



Fully Featured:

- Light weight & compact size
- 5.6" CCTV TFT LCD Monitor
- NTSC/PAL auto recognition
- Two BNC inputs / One BNC output
- Audio jack input & output
- Test pattern generator (colorbars/crosshatch/RGB/Dot)
- OSD Multi-language support
- Carrying strap and travel case
- Rechargeable battery and AC adaptor
- Ideal for CCTV installation, on-site demonstration and testing
- Last memory for settings when powered off
- Power saving while no signal input




RS5.6TFT-2

5.6" LCD Test Monitor
with Test Pattern Generator


RS5.6TFT-2

5.6" LCD Test Monitor
with Test Pattern Generator

Test Pattern Generator




Side View



Description	
1	Power mode switcher (ON / OFF / Charge)
2	Power input jack (DC IN)
3	Audio input/ output
4	Video OUT
5	Video1 / Video 2 IN

Back View:



Description	
1	Rechargeable battery

Packing List

- . 5.6 TFT LCD Monitor x 1
- . Travel case with carrying & waist strap x 1
- . AC adaptor x 1
- . Rechargeable Li-poly battery x 1
- . 12VDC vehicle cigar lighter charger x 1
- . 3.5" stereo jack to RCA jack cable x 1
- . User Manual x 1

MODEL	RS5.6TFT-2	
LCD panel spec.	LCD display	5.6" Active Matrix TFT LCD
	Screen size (Viewable size)	112.9mm (H) x 84.7mm (V)
	Max. resolution	640(H) x 480(V) (4:3)
	Lamp life time	20,000 hrs
	Dot pitch	0.0588(W) x 0.1764(H)mm
	Contrast ratio	500:1 Typ.
	Brightness	200 cd/m ² (TYP.)
	Response time Tr/Tf	15/10ms (TYP.)
	Viewing angle L/R	70°/70°
	Viewing angle Up/Down	50°/70°
Front Control	Power on/off, Power/Recharge LED indicator, SOURCE, Up (Volume Increase) Picture (OSD menu), Down (Volume Decrease)	
Display mode	Video 1, Video 2, Test pattern	
OSD menu	Video	Language, Auto Off, Contrast, Brightness, Colour, Tint, Sharpness, Recall
Signal connector	Input	2 x BNC Inputs (1.0Vp-p75 Ω); 1 x Audio Input (3.5 Ω stereo Jack)
	Output	1 x BNC Outputs (2.0Vp-p75 Ω); 1 x Audio Output (3.5 Ω stereo Jack)
Audio speaker	1W (Max.)	
Environment considerations	Operating condition	Temperature: 0°C ~ 40°C, Humidity 20% ~ 80%
	Storage Condition	Temperature: -20°C ~ 60°C, Humidity 15% ~ 85%
Power Input	DC 12V / 1.5A	
Power Consumption	11.25W (without battery charge) 19.875W Max (with)	
Power Supply	AC100V ~ 240V 50/60Hz	
Dimension	Net (WxHxD)	190 x 126 x 44.5mm
	Packing (WxHxD) (1pcs/Box)	256 x 175 x 116mm
	Weight	N.W.: 1.2kgs, G.W.: 1.6kgs
Stands/bracket supported	1/4" standard screw mount on bottom	
Rechargeable Battery Condition	Lithium battery (7.4V / 2600mAh)	
Safety	FCC, CE(EMC/LVD), UL, BSMI, CCC	
Material	FrontPanel	Plastic
	RearCover	Plastic
Optional accessories	Rechargeable battery	BT-088269

specification subject to change without notice