

TWINFLEX[®]pro

SO SMART, YOU

MIGHT CALL IT

INTELLIGENT



Fike[®]

THE RELIABLE FIRE PROTECTION SYSTEM YOU CAN COUNT ON.

A conventional 2-wire fire alarm system is often the natural choice for smaller applications or where budget constraints exist. Fike's TWINFLEXpro 2-wire fire alarm system has long been known for its adaptability and cost-effectiveness within a variety of applications, big or small ... making it one of the most flexible products on the market. Building on those strengths, and designed for ease of use and state-of-the-art monitoring, the LPCB-Approved TWINFLEXpro is the next generation in 2-wire fire alarm reliability.



THE INNOVATIVE TWINFLEXpro, 2-WIRE PANEL IS SUITABLE FOR A VARIETY OF INSTALLATIONS.

This versatile fire alarm panel incorporates Fike's Multipoint detection system using smoke and heat detectors with built-in sounder, allowing the whole system to be installed using only one pair of wires per zone.

That means easier, faster installations AND cost savings.

- 4 line x 20 character LCD display
- Ability to differentiate between callpoint or detector alarms
- Checkpoint alarm verification feature
- Available in 2, 4, and 8 zone panel versions
- Highlighted selection menu
- Event log storing up to 500 events
- 3 enhanced test modes
- Allows detectors and sounders to be installed on the same pair of wires
- Up to 32 devices per zone
- Built-in EOL capability in all devices
- 7 modes of detection

TWINFLEXpro

NOW with LPCB Approval

TWINFLEXpro PROTECTS:

- | | |
|----------------------|------------------------|
| • Schools | • Restaurants |
| • Nursing Homes | • Retail Stores |
| • Bed and Breakfasts | • Historical Buildings |
| • Hotels | • Local Museums |
| • Apartments/Flats | • Office Buildings |





MULTIPOINT DETECTOR

Using patented, advanced optical scatter sensor design and sophisticated electronic technology, Fike delivers reliable smoke and/or heat detection ... significantly reducing the risk of nuisance fire alarms.

- 7 modes of fire detection including combined smoke/heat
- Optional built-in sounder in a single device
- Self-calibrates every 6 hours
- Continuously monitors for dust contamination
- Economical, disposable optical chamber for easy replacement

SMOKE 1

Used where ionization detectors are normally fitted, especially when there are high ceilings or a risk of free burning fires (chemical stores etc), or fires that need to be detected extremely quickly.

SMOKE 2

Used where optical detectors are normally fitted, when there is a risk of a smouldering fire and for escape routes.

SMOKE 3

Designed for use in areas that are prone to nuisance alarms. The reduced sensitivity linked with a time delay feature means that a higher concentration of smoke needs to be present for a constant time period before a fire decision is made.

HEAT 1

(Rate-of-Rise) – Used where a standard rate-of-rise detector would normally be used.

HEAT 2

(Standard Fixed Temperature – 58°C / 136°F approximately) – A standard fixed temperature heat detector, suitable for domestic kitchens, etc.

HEAT 3

(High Fixed Temperature – 90°C / 194°F approximately) – High fixed temperature heat detector suitable for boiler rooms, commercial kitchens, etc.

MULTIPOINT AND TWINFLEXpro

Using the Multipoint detector with sounder as part of the TWINFLEXpro 2-wire fire alarm system means that when a detector is wired in, a sounder is also, with no extra wiring required. This greatly reduces the number of points that need to be installed – and the time it takes to install!

In fact, with the TWINFLEXpro exclusive 2-wire design, installation savings can be as high as 40%!

Multipoint offers 7 different modes of detection, which means one device can suit multiple applications.

Whatever type of detection is required, it can be selected with an easy flick of a switch at the time of commissioning.

- Sounders can be run on the same pair of wires as detectors/callpoints
- No extra devices needed for audible warning
- Can differentiate between callpoint and detector alarms
- Two sound volumes easily selectable by switch





Early warning fire alarm verification is often crucial. The disruption to business and costs associated with responding to false alarms can be enormous. The TWINFLEXpro offers

checkpoint alarm verification technology, which can help eliminate nuisance or false alarms.


CHECKPOINT ALARM VERIFICATION

Checkpoint alarm verification technology has the ability to select a confirmation period for individual detectors and confirm if the smoke/heat detected is an actual fire – and not a false alarm.


Using the built-in alarm confirmation feature, until an alarm has been confirmed within an individual area, only that area is evacuated. At the same time, if an alarm is confirmed in a common area, the device initiates a full alarm evacuating all surrounding areas. This unique conventional panel feature is vital where two-stage alarms are required.

For example – when an alarm is indicated by an individual detector, the sounder for that device is activated and the control panel carries out the configured number of confirmation checks on that specific zone. If the alarm is confirmed, the control panel enters the fire state and all additional notification devices are activated throughout the facility. If the detector alarm is rejected, the sounders on the zone are silenced, and the detector in alarm is reset.

For safety, activating a callpoint will override any delays or confirmation settings.



TWINFLEX[®]pro



TWINFLEX^{pro}

FIKE TRADITION

OVER 65 YEARS IN PROTECTING

LIVES AND ASSETS.

OUR COMMITMENT

THE RIGHT SOLUTION THAT

EXCEEDS YOUR EXPECTATIONS.



FIKE GLOBAL MANUFACTURING, SALES AND SERVICE

EUROPE

FIKE SAFETY TECHNOLOGY
Cwmbran, United Kingdom
Tel: +44 (0) 1633 865558
Email: fstinfo@fike.com

ASIA

FIKE ASIA PACIFIC SDN BHD
Selangor Darul Ehsan, Malaysia
Tel: +60-3-7859-1462
Email: fikeap@fike.com

AMERICAS

FIKE CORPORATION
Blue Springs, MO, USA
Tel: +1-816-229-3405
Email: fpssales@fike.com

MIDDLE EAST

FIKE CORPORATION DUBAI
Dubai, UAE
Tel: +1-816-229-3405
Email: fikedubai@fike.com

**FIKE LATINA LTDA
(MERCOSUR)**

Jundiai, Brazil
Tel: +55-11-4525-5900
Email: vendas@fike.com.br

**CARIBBEAN, CENTRAL,
SOUTH AMERICA (CCSA)**

Houston, TX, USA
Tel: +1-281-895-8342
Email: ccsasales@fike.com



Fike[®]

WWW.FIKE.COM

TWINFLEX^{pro}, Multipoint, Fike and Fike Corporation are trademarks or registered trademarks of Fike Corporation and its subsidiaries. All other trademarks, trade names or company names referenced herein are the property of their respective owners.

©Copyright 2011, Fike Corporation. All rights reserved. Form No. B9121UK 1011