

Break glass call point

An attractive range of break glass call points, available as a standard version for interior use, or a weatherproof version for outside use or where adverse conditions apply. A protective plastic coating on the glass prevents operator injury and inhibits the release of glass fragments, enabling the call point to be operated by firm thumb pressure. A hammer is not required.

The call point is tested by means of a test key (supplied with each unit) without the need to unfasten the cover. The flush call point is suitable for mounting on a BS4662 switch/socket box, while the surface call point is supplied with a plastic box.

Clearly marked terminals are provided for connections either via an internal diode for MF9300 systems or a 470 Ohm resistor for all other Menvier systems.

The call points are manufactured in red thermoplastic and fully comply with BS5839: Part 2.

Weatherproof break glass call point

This call point is identical in operation to the standard call point. The MBG917R weatherproof unit is supplied with gasket set, providing sealing of the back box to IP65.

The call point fully complies with BS5839 Part 2.

Hinged polycarbonate flap

In order to reduce the likelihood of mischievous operation in areas open to the general public, the MBG HCC clear protective flap has to be hinged upwards in order to expose the glass element.



Specification

MBG914 Break glass call point	
Operation	Open Circuit Contacts
Contact Rating	24V DC (resistive)
Dimensions	87 x 87 x 23.5mm (visible on flush unit) 87 x 87 x 56.5mm (including surface box)
Mounting	Flush – Standard BS4662 switch/socket box
Finish	Red Thermoplastic
Weight	0.18kg including plastic box
MBG917 Weatherproof break glass call point	
Operation	Open circuit contacts
Contact rating	24V DC
Dimensions	87mm x 87mm x 56.5mm
Mounting	Surface
Finish	Red Thermoplastic
Weight	0.2kg

Other colours and optional legends available to special order, also plastic elements for use in the food industry.

Order Codes

MBG913	Flush Mounting Call Point
MBG914	Surface Mounting Call Point (with plastic box)
MBG118	Spare glasses (pack 5)
MBG119	20mm earth continuity links (pack 5)
MBG917	Weatherproof surface call point
MBG HCC	Hinged polycarbonate flap
MFBKEY2	Pack of 5 spare keys
ZMBGBOX	Spare back box for MBG914, 913 and 613