

## external vandal resistant colour dome camera



### features

- ✓ sharp 1/4" interline transfer colour CCD
- ✓ tamper and vandal resistant aluminium housing
- ✓ vandal resistant clear 75mm polycarbonate bubble
- ✓ surface mount, 360° view
- ✓ automatic gain control
- ✓ backlight compensation
- ✓ wide range of lens options, 3.6mm fitted as standard
- ✓ ip-65 rated

### technical data

image sensor	sharp 1/4-inch interline colour CCD
horizontal resolution	350TVL colour – 512 x 582 pixels
electronic shutter	1/50 – 1/100,000 seconds
sensitivity	1.0 lux @ f1.2
signal to noise ratio	greater than 45dB (agc off)
white balance	automatic
lens options	2.1mm to 16mm
power consumption	100mA
video output	1V p-p ~ 75Ω
dimensions	138mm diameter x 97mm high
power supply	12V ± 10%
operating temperature	-10° C ~ +50° C
operating humidity	10% ~ 90%

#### Genie CCTV Limited

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT

tel: +44(0) 1707 330541

fax +44(0) 1707 330543

website: [geniecctv.com](http://geniecctv.com)

email: [info@geniecctv.com](mailto:info@geniecctv.com)