

8-channel triplex digital video recorder



features

- ✓ **triplex – simultaneous record, playback and backup**
- ✓ **variable HDD configuration from 250Gb to 1Tb**
- ✓ **on-board Ethernet network interface card**
- ✓ **integral CD re-writer for backup**
- ✓ **easy navigation via on-screen display (OSD) menu**
- ✓ **automatic system recovery after power interruption**
- ✓ **backup via USB memory stick**
- ✓ **comprehensive remote viewing and management software**
- ✓ **PTZ control via built-in RS485 port**
- ✓ **includes IR remote controller**

technical data

| | |
|---------------------------------|--|
| System Information | Embedded Linux OS, 266MHz CPU, 128Mb RAM |
| Video Input | 8 x Composite BNC |
| Video Output | 2 x Composite BNC, 1 x VGA and 1 x S-Video |
| Audio | 4 x Channel Input, Single Channel Output |
| Alarms | 4 x Alarm Inputs, 2 x Alarm Relay Outputs |
| HDD Size | 250Gb to 1Tb (2 x HDD spaces available) |
| Network | 10/100Mb Ethernet Base-T, via RJ45 Connector |
| Motion Detection | Motion Sensitivity and Motion Area per Camera |
| Recording Speed | 100fps PAL |
| Recording Format | MPEG4 Compression |
| Recording Resolution/Image Size | 352x258, 704x288 or 704x576 (3-5Kb, 5-10Kb or 10-16Kb) |
| Display Speed | 200fps PAL |
| Screen Modes for Live Display | 1, 4, 9, and Picture in Picture |
| PTZ Control | Pan/Tilt/Zoom/Focus/Iris |
| System Recovery | Auto-Reboot and Journaling File Entry with Auto Scan |
| Functions Available | Status LED's, Access Control by Password, Event Log Viewer Pre-Alarm Multi-channel Playback, Digital Zoom, Covert |
| System Operation | Buttons on Front Panel or IR Remote Controller |
| Environmental | Operating Temperature 5~40°C, Humidity 20~85% RH |
| Power | AC 115-230V, 50/60Hz – Switch Selectable |
| Dimension and Weight | 380mm(W) x 66mm (H) x 370mm (D), 6Kg |

Genie CCTV Limited

Unit D, 26 watchmead, welwyn garden city, herts. AL7 1LT

tel: +44(0) 1707 330541

fax +44(0) 1707 330543

website: genieccctv.com

email: info@genieccctv.com