

rack mounting regulated power supply



Features:

- 16 x Regulated AC24V outputs
- 230V AC Input
- Line condition LED on mains input
- Individual PTC (Positive Temperature Coefficient) output protection
- Individual current protection
- Automatic reset following short circuit condition
- Built-in "no fuse" break for short circuit protection
- Toroidal transformer for high efficiency and low temperature operation
- Standard 1U 19-inch rack mount
- Supplied with mains IEC lead

Specification:

Input Voltage	230V AC
Output Voltage	AC24V @ 8A
Output Current	Nominal 500mA per Channel
Output Trip Current	1A
Output Current Protection	1.1A – Max. 2.5A for 4 seconds
Short Circuit Trip	0.2 seconds
Surge Protection	Built-in
Output Reset	Automatic
Reset Time	1 second
Input Connector	IEC Socket
Output Connectors	Screw Terminal
Dimensions (mm)	437mm x 170mm x 44.5mm
Weight	4Kg
Finish	Black Powder Coated Steel
Storage Temperature	-30° ~ 70°C
Operating Temperature	-10° ~ 45°C

Genie CCTV Limited

Unit D, 26 watchmead, welwyn garden city, hertfordshire AL7 1LT
 tel: +44(0) 1707 330541 fax +44(0) 1707 330543
 website: genieccctv.com email: info@genieccctv.com