

## high resolution day/night **DNR** bullet camera with integral infra-red LED's



### features

- ✓ High Resolution 540TV lines in Colour
- ✓ Impact Resistant Housing
- ✓ 2.9 -10mm Auto Iris Varifocal Lens
- ✓ **TRUE** Day/Night, Mechanical Cut-Filter
- ✓ 33-piece Infra-Red LED Assembly with CDS Sensor
- ✓ On Screen Display (OSD) Menu
- ✓ **DNR (Digital Noise Reduction)** – Four Levels of Noise Reduction
- ✓ Saves up to 70% HDD Storage with **DNR**, Using MPEG 4 Codec
- ✓ Selectable Electronic Shutter Control, FLK/ESC/Manual
- ✓ Selectable White Balance, ATW/AWC/Manual
- ✓ Selectable Back Light Compensation, H/M/L/Off
- ✓ Selectable Gain Control, H/M/L/Off
- ✓ Sens-Up – Maintains Luminance Levels in Low Light x128
- ✓ Privacy Masking – 4 Programmable Zones
- ✓ Mirror Function – Horizontal Image Inversion
- ✓ Camera Title
- ✓ Optional Remote Controller (Product Code - ZRC) for Menu Set-Up
- ✓ IP65 rated
- ✓ Dual Voltage, DC12V/AC24V
- ✓ Fully Cable Managed Bracket
- ✓ Sunshield

### Genie CCTV Limited

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT  
tel: +44(0) 1707 330541 fax +44(0) 1707 330543  
website: [geniecctv.com](http://geniecctv.com) email: [info@geniecctv.com](mailto:info@geniecctv.com)

**technical data**

Image Sensor	Sony 1/3-inch Super HAD CCD
Horizontal Resolution	540 TV Lines Colour
Effective Pixels	752 (H) x 582 (V)
Scanning System	2:1 Interlace
Synchronisation	INT or LL Selectable
Frequency	15.625KHz (H), 50Hz (V)
Video Output	CVBS 1.0V p-p ~ 75Ω
Signal to Noise Ratio	Greater than 50dB (AGC off)
Sensitivity	0.7Lux F1.8 (50 IRE) Colour 0.1Lux F1.8 (50 IRE) Monochrome
Electronic Shutter	Automatic Manual - (1/50 to 1/100,000 second) Flickerless - 1/100 Second
Gain Control	Selectable Off/Low/Middle/High
White Balance	ATW/AWC/Manual (1,800°K ~10,500°K)
Digital Noise Reduction	Selectable Off/Low/Middle/High
Backlight Compensation	Selectable Off/Low/Middle/High
Lens	2.9-10mm Varifocal
Iris Control	Automatic
LED	33-piece LED Assembly with CDS Photosensor
On-Screen Display	Built-In
Camera Title	Selectable On/Off - Maximum of 15 Characters
Privacy Zone	Selectable On/Off - Up to 4 Programmable Privacy Zones
Power consumption	800mA Maximum with IR LED's ON using DC12V
Power supply	DC12V or AC24V
Dimensions	140mm x 75mm diameter, without Sunshield & Bracket
Operating temperature	-10° C ~ +40° C
Operating humidity	30 ~ 80% RH Max.
Weight	900g

**Genie CCTV Limited**

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT  
tel: +44(0) 1707 330541 fax +44(0) 1707 330543  
website: [geniecctv.com](http://geniecctv.com) email: [info@geniecctv.com](mailto:info@geniecctv.com)