



## features

- ✓ 4 –channel active receiver unit with individual gain adjustments
- ✓ transmission up to 1.5Km in colour, 2.4Km in monochrome
- ✓ 4-way terminal block for video input
- ✓ 4 x BNC connector for video output
- ✓ built-in transient protection and ground lifting
- ✓ for use with Category 5, 5e or 6 UTP cable
- ✓ supplied with 12V DC power supply

## technical data

nominal input impedance	100-105 $\Omega$ (balanced)
nominal output impedance	75 $\Omega$ (unbalanced)
input connector	4 position terminal block
output connector	4 x BNC connector
video input	1V p-p
video output	1V p-p
cable type	Category 5, 5e or 6 UTP (24AWG)
power	12V DC, max 150mA
EMI standard	meets FCC class B, CE
case dimensions	133mm (w) x 115mm (d) x 43mm (h)
case material	metal, black in colour
operating temperature	0 $^{\circ}$ C ~ +40 $^{\circ}$ C
operating humidity	20% ~ 80%

### Genie CCTV Limited

Unit D, 26 watchmead, welwyn garden city, hertfordshire AL7 1LT

tel: +44(0) 1707 330541

fax +44(0) 1707 330543

website: [geniecctv.com](http://geniecctv.com)

email: [info@geniecctv.com](mailto:info@geniecctv.com)