



Fig. 1- KP1 Series Panic Button



Fig. 2 - KP2 Series Panic Button



Fig. 3 - KP3 Series Panic Button

	Model		
	KP1	KP2	KP3
Grade 2 Class II	●	●	●
Reed NO/NC	●	●	-
Latch	●	-	●
Non Latch	-	●	-
Metal Key	●	-	●
Spare Keys to order	●	-	●
Micro-Switch CIO	-	-	●
Plastic	●	●	●
St/Steel (S)	●	●	●
Brass (B)	●	●	●
Knockouts End	1	1	1
Knockouts Back	-	-	-
Knockouts Side	-	-	-
Dimension	Length 91	Width 63.5	Height 29mm
<u>Options</u>			
Smooth Buttons	●	●	●
Ridged Buttons	●	●	●

**Description:**  
Single End Push Panic Button

**Materials:**  
ABS / Acetal

**Temperature Range:**  
-40°C - +50°C

**Tampers:**  
Stainless Steel  
Metal Key Provided inside

**Switching Current**  
500mA Max DC  
500mA Max AC

**Contact Material:**  
Rhodium

**Indicator:**  
Flag Type

**Voltage Range:**  
1 – 100v DC  
125v AC Max

**Colours:**  
Plastic - White (No Suffix)  
Plastic - Black (Suffix B)

**Finishes:**  
Plastic, Brass (B), Stainless Steel (S)

**KNIGHT**  
**PLASTICS LTD**  
email: [info@knightplastics.com](mailto:info@knightplastics.com)

Unit 1 Clydesmuir Rd. Ind. Estate  
Cardiff UK CF24 2QS  
Tel: 0 (00 44) 29 20 48 81 29  
Fax: 0 (00 44) 29 20 48 91 32

Drawing No: **KP1-3 Series  
Panic Button**

Drawn: Chris Moorman

Date: 17/10/06

All units in mm  
Do not scale



The portrayed information is © Knight Plastics Ltd  
All cases of ™ Infringement will be persued.