

## CCTV RF Modulator



### features

- ✓ converts a composite PAL video signal to UHF signal
- ✓ video and audio modulator
- ✓ channels 21-69 (471 – 862MHz)
- ✓ digital channel display
- ✓ selectable 75Ω termination
- ✓ suitable for domestic television equipment
- ✓ built-in test signal generator for set-up and tuning
- ✓ supplied with PSU, UHF Aerial Lead & BNC to Phono Adapter

### technical data

|                       |                                  |
|-----------------------|----------------------------------|
| input signal          | composite video 1V p~p           |
| input video connector | RCA phono or SCART               |
| input audio connector | RCA phono or SCART               |
| output signal         | UHF (PAL-I / PAL-G) 471 ~ 862MHz |
| output connector      | UHF                              |
| power supply          | regulated 12V DC                 |
| power consumption     | less than 200mA                  |
| dimension             | 800mm x 60mm x 45mm              |
| weight                | 80g                              |
| material              | Black ABS – Internal Use Only    |

#### Genie CCTV Limited

Unit D city park, 26 watchmead, welwyn garden city, herts AL7 1LT

tel: +44(0) 1707 330541

fax +44(0) 1707 330543

website: [geniecctv.com](http://geniecctv.com)

email: [info@geniecctv.com](mailto:info@geniecctv.com)