

LCD COLOUR MONITOR

Model No. LM413

4" TFT LCD PAL & NTSC Colour Monitor - Metal Cased with LED Backlight (also available in 5.6" LM6323 & 7.0" LM7323 versions).



The LM413 with TFT active matrix technology with LED Backlight, offers a sharp and high contrast display. With a metal case, it makes it ideal for rugged applications. With universal application potential, the LM413 is ideal for Surveillance Systems, Reverse Monitoring Systems and Multimedia Video applications. An audio input also enables sound reception via headphones. A "C" mount thread in the bottom of the unit is for easy mounting.

SPECIFICATIONS:

- High resolution 112,320 pixels 480x234 (WxH).
- Active Area: 82.1 x 61.8mm (HxW). Dot Pitch: 0.264 x 0.171 (HxW) mm
- Video system PAL & NTSC, Brightness 250 cd/m², Contrast Ratio 150:1
- Controls: Front - Brightness, Contrast and Volume Thumb wheel
- Controls: Side - Picture reverse L/R & Video 1/2 switches
- Audio output via Headphone socket on front cabinet
- Power Source: 12V DC, 500mA, 5 Watts approx.
- Dimensions: 141.2 x 115.4 x 38.4 (WxHxD)mm. Carton: 195x52x143 (WxHxD)mm
- Temp: Operation: +0°C - +60°C Storage: -20°C - +40°C
- Finished in black Weight: 0.40 kgms. Carton: 0.45 kgms

Connections: Input: Video 1 & Video 2 Phono Socket. Audio Phono Socket

Output: Video Phono Socket, Earphone 3.5mm stereo jack (2 x mono)

Standard Accessories

None. Unit only

Optional Accessories

Audio Video lead

2 x RCA Phono -

3.5 mm stereo jack

AC Adaptor

DC Adaptor

All information correct at time of going to press • Design and specification are subject to change without prior notice.E&OE.

Product Shop International Ltd

PO Box 5503, Newbury, Berkshire, RG14 6RB. UK.

e-mail: sales@productshop.co.uk Website www.productshop.co.uk

Tel: +44 (0) 8708 50 55 55 Fax: +44 (0) 8708 50 55 44

Registered office: As above. Registered No. 3852764 VAT No. GB 727 0478 29