

video, audio & power line driver kit



features

- ✓ transmits video, audio, alarm, RS485 and 24V ac power over a single coaxial cable
- ✓ real-time transmission up to 800 metres (no dc power)
- ✓ consists of 2701 Sender and 2701 Viewer units
- ✓ LED indicators on both units to display status
- ✓ built-in transient protection
- ✓ compact size and weight

technical data

Video Input/Output	1V p-p 75Ω PAL
Video Bandwidth	5.5MHz
Signal to Noise Ratio, Video	50dB
Audio Input Signal	3.0V p-p 100K Ω, Maximum
Gain of Audio Output	0dB ± 3dB, 600Ω
Audio Bandwidth	50Hz ~ 10KHz
Signal to Noise Ratio, Audio	46dB
Alarm Input, 2701 Sender	1 x Alarm Sensor
Alarm Output, 2701 Viewer	1 x NO, NC or TERM (390 Ω), Contact Rating 1A, 30VDC
RS485 Data Rate	0 ~ 38K bps, Half Duplex
DC Power Output , 2701 Sender	24V ac 1.2A maximum
Power Adapter Input	90V ~ 240V ac
Power Adapter Output	Variable Power Supply 18V ~ 38V dc
Reverse Polarity Protection	Yes
Cable types supported	RG59, CT125, RG6, RG11, 5C-2V, 3C-2V
Dimensions 2701 Sender	100mm x 75mm x 27mm, Weight 225g
Dimensions 2701 Viewer	100mm x 75mm x 27mm, Weight 210g