

3800CRGGMNM

HID DESFire EV1 and HID Prox Combo, 8KB Memory, ISO, Prgm SIO, Default NXP keys,
PVC(HID Prox and MIFARE DESFire EV1 Combo Contactless Smart Card 8k bytes memory,



3800CRGGMNM

HID DESFire EV1 and HID Prox Combo, 8KB Memory, ISO, Prgm SIO, Default NXP keys, PVC(HID Prox and MIFARE DESFire EV1 Combo Contactless Smart Card 8k bytes memory,

Technical specifications

Technology

Credential type	Multi-technology
Credential operating frequency	125 KHz, 13.56 MHz
Support technology	MIFARE DESFire EV1 (CSN) 13,56 MHz
Support technology 125 KHz	HID Prox

System

Reading distance	5 to 10 cm
Custom data model	No
Memory size	8K
No. of Mifare bytes CSN	7 Byte (S70)
Card slot punch	No

Printing

Direct surface printing	Yes
Thermal transfer printing	Not recommended

Ordering information

Minimum order quantity	100
Cards/tags in package	1
Special card order form required	Yes

Physical

Surface cover	Glossy
Material	PVC
Form factor	CR80 (Credit)
Physical dimensions	54 x 86 x 1 mm
Net weight	5 g
Shipping weight	13 g
Colour	White

Environmental

Operating temperature	-40 to 50°C
Storage temperature	-40 to 50°C
Relative humidity	5 to 95% noncondensing

Standards & regulation

Compliance	RoHS
------------	------

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

16 April 2019 - 4:32



**United
Technologies**

Climate | Controls | Security