

reader



MIFARE® Smart Card Reader

Stylish and fully featured MIFARE® smart card readers from TDSi. These readers are extremely cost-effective MIFARE® serial number readers available housed in a robust, fully encapsulated ABS enclosure allowing it to be mounted both indoors and out.

The main industry standard oututt formats are supported allowing direct connection to all of the current range of TDSi access control units as well as access control panels from other manufacturers.

MIFARE® CSN reader

SPECIFICATIONS

TDSi Part No.	5002-0440
Dimensions	42 x 104 x 18 mm
Weight	160 g
Operating Environment	-5 °C to +60 °C, 0 to 95 %RH (non-condensing)
Power Supply	6 to 14 VDC, 120 mA
Operating frequency	13.56 MHz (nominal)
Card technology	ISO14443-A: MIFARE Standard (1k) MF1 ICS50, MIFARE (4k) MF1 ICS70
Sounder	Integral
LEDs	Green and Red
Read range	<50 mm
Output formats	Magnetic stripe, 26-bit Wiegand

ORDERING INFORMATION

Part Number: 5002-0440

Description: TDSi MIFARE® Serial Number Smart Card Reader

Part Number: 2920-3000

Description: ISO 1K MIFARE® card – plain white.

Part Number: 2920-3001

 $\textbf{Description:} \ \mathsf{ISO} \ \mathsf{4K} \ \mathsf{MIFARE} \\ \texttt{@} \ \mathsf{card-plain} \ \mathsf{white}.$

Part Number: 2920-3002

Description: ISO 1K MIFARE® card – white with serial number printed.

Part Number: 2920-3003

Description: ISO 4K MIFARE® card – white with serial number printed.

FEATURES & BENEFITS

Serial number reader version

Provides a quick and easy solution.

Compatible with ISO 14443-A standard for 13.56 MHz contactless smart card technology

Use one card for all of your applications including cashless vending, library, POS and car park.

Stylish, elegant case design

Fits with any surrounding without looking out of place.

Fully encapsulated design

Provides maximum protection against water ingress making it suitable for mounting both indoor and out.

Integral LEDs

Provides clear visual indication of access status.

In-built sounder

Gives unambiguous feedback of card reads.

Choice of output options

Allows connection to the majority of access











TDSi UK
Unit 10 Concept Park,
Innovation Close,
Poole,
Dorset BH12 4QT
United Kingdom
t: +44 (0)1202 723535
f: +44 (0)1202 724975

Immeuble ATRIA, 2 rue du Centre 93160 NOISY LE GRAND, France t: +33 (0)1 58 84 20 90 f: +33 (0)1 58 84 20 91 e: infos@tdsi-france.com

TDSi France

TDSi China Rm 103, 1 Bld, Shangsha Innovation Science & Technology Park, 9283 Binhai Road, Futian District, Shenzhen 518048, P.R.China t: 86-755-82535725, 82535720 f: 86-755-82535770