

DUOX VEO-XS DDA 4.3" MONITOR

**Reference:** 9458

Hands-free DUOX VEO-XS monitor is characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made...

DESCRIPTION

Hands-free DUOX VEO-XS monitor is characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made of high impact ABS plastic. Texturised finish for easy cleaning and ultraviolet protection. VEO-XS WIFI incorporates a 4,3" (16:9) panoramic color TFT screen. Its balanced design of pure lines is distinguishing, modern and minimal.

TECHNICAL SPECIFICATIONS

GENERAL CHARACTERISTICS

- Technology: DUOX (non-polarised 2 wire full digital system)
- Audio/Video system: Audio/Video Color
- Set-up (Installation): Surface mounted (order connector ref. 9447 separately)
- Hands-free communication: Yes
- Press-to-talk communication configurable: Yes
- Induction loop included: Yes
- Screen dimensions: 4,3" (Panoramic 16:9)
- Screen resolution (H x V): 480 x 272
- Color of the product: Matt white
- Number of pushbuttons: 5
- Kind of pushbuttons: Mechanical (silicon)
- Number of leds for lighted indications: 4 (red, blue, green with different states and white for Wifi)

PROGRAMMING OF THE TERMINAL ADDRESS

- From the terminal: From the OSD menu
- From the outdoor panel or guard unit: Yes
- From the outdoor panel throughout the apartment door bell: Yes



FEATURES

- Automatic picture capture when the visitor calls (PHOTOCALLER): Yes (1 photo/call, until 150 photos, 320 x 240 pixels). Disabled by default. To be enabled by the user.
- Guard unit call: Yes (by means of the door release button)
- Auto-on: Yes (with 3 outdoor panels/cameras)
- OSD menu: Yes
- Additional function F1: Yes (Button F1 sends a negative and/or command)
- Additional function F2: Yes (it only sends command, no negative)
- Apartment door bell differentiated from the outdoor panel: Yes
- Connection for additional devices (call extension, light/buzzer activator, etc.): Yes (ref. 2040, ref. 2438, ref. 3257)
- Additional terminals on the same address: Yes, max. 2 additional terminals (additional power supply can be required)
- Doormatic (automatic door release for offices, etc.): Yes (configurable until 12h). Green Led ON.
- Possible to remotely upgrade the monitor firmware version: Yes

ADJUSTMENTS

- Date and time: Yes (manual & automatically from the internet via wifi)
- Ring tones selection :Yes (5)
- Call volume control: Yes (10 levels by OSD menu and sliding wheel)
- Do-not-disturb mode: Yes (by OSD menu) + Red Led indication
- Audio volume control: Yes (10 levels by OSD menu and sliding wheel)
- Brightness, color and contrast control: Yes (by OSD menu)

TECHNICAL FEATURES

- Product dimensions (width x height x depth) mm: 125 x 165 x 21
- Time to answer or open the door since the call is done: 30 s.
- Conversation time: 90 s.
- Conversation privacy: Yes
- Voltage: 18 Vdc
- Maximum consumption: 6.9 W, 14.4 W (if the induction loop is activated)
- Standby consumption (paired and connected): 1.3 W
- Working temperature (°C); Humidity: [-5°C, +40°C]; [0%, 90%]
- Line adaptor included in the terminal: Yes (A, C, default position OFF)
- Connections: Bin, Bin, Bout, Bout, -, A+, F1, T

ACCESORIES

Ref. 9447: DUOX VEO/VEO-XS MONITOR CONNECTOR

Ref. 9420: VEO-XS MONITOR DESKTOP SUPPORT

Ref. 3388: UNIVERSAL FRAME 120X240

Ref. 3389: UNIVERSAL LARGE FRAME 210X240

Weight: 0,2841 kg

Size of product when packed: 17x12,8x4 cm

EAN 13: 8424299094588