

Product Data Sheet

ATS1151

ATS Aluminium Keypad With 3 LED

Remote Arming Stations

The ATS 1151 is part of the Remote Arming Station family for the advisor MASTER security system. The RAS family consists of a range of keypads and card readers which can be used in different environments, in and out-door. It can be used for opening doors and arming/disarming areas. In an easy way, the ATS1151 gives a status overview from your security system with both visual and audio indicators.

Product Overview

The keypad can be mounted beside the door to be controlled. The electronics are mounted in an aluminium housing which is designed to resist weather and vandalism. The keys are engraved stainless steel. It is suitable for all kinds of environments, indoors or outdoors, and has a built-in heater to keep the unit ice-free. If the keypad is opened, a tamper contact will transmit an alarm to the controller. The keypad is surface mount only.

Functionality

The ATS system permits the programming of PIN codes of up to nine(9) digits.

The keypad can be used to:

- Open a door for valid codes during certain hours
- Arm/disarm an intruder alarm system

The keypads have LED indicators to give the user information about the status of the system. Each access point in the system controlled by the keypad can be programmed separately.



Standard Features

- For access control where code only is requested
- Robust design
- Tamper proof
- Keypad to controller configuration
- For indoor or outdoor applications



ATS1151

ATS Aluminium Keypad With 3 LED

Specifications

Supply voltage	12 VDC (from the controller)
Current consumption	
Indoor	45 mA
Outdoor (heater active)	85 mA
Cable	
Keypad - Controller	4 wires, twisted pair, shielded
Operating temperature	-25 °C to +70 °C
Dimensions (H x W x D)	96 × 67 × 28 mm
Weight	226 g
Communication	RS485 ATS dataloop

Ordering Information

Part No.	Description
ATS1151	ATS Aluminium Keypad With 3 LED

