

ATS1458W

(5 PACK) Secure ATS sBand White

Product overview

The silicone wristband in white color offers a robust solution for a secure environment where card data is protected with Mifare Desfire EV2 encryption. It can be used in secure mode with ATS118x range readers and ATS1136 keypad.

When used on other Mifare Readers the standard Mifare 7-byte CSN is provided instead of the secure card data.



Details

- Attractive designed silicone wristband in white color
- Card data secured by AES encryption
- Mifare Desfire EV2 encrypted application

ATS1458W

(5 PACK) Secure ATS sBand White

Technical specifications

Technology

Credential type	Smart card
Credential operating frequency	13.56 MHz
Supported technology 13.56 MHz	Mifare DESFire EV2 (CSN), MIFARE DESFire EV2 (UTC)

System

Reading distance	Secure mode: between 1 - 5 cm Unsecure mode: between 2-5 cm Distance may vary based on reader
Custom data model	No
Memory size	2K
Supported readers	ATS ATS118x Secure Readers

Printing

Direct surface printing	No
-------------------------	----

Ordering information

Minimum order quantity	1
Cards/tags in package	5

Physical

Material	Silicone
Form factor	KeyFob
Physical dimensions	100 x 50 x 75 mm
Net weight	80 g
Shipping weight	80 g
Colour	White
Card Label	Serial number

Environmental

Operating temperature	-10 to +85°C
IP rating	IP68

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 25 November 2019 - 14:04



**United
Technologies**

Climate | Controls | Security