

Class D Solid Core LSZH LOW SMOKE ZERO HALOGEN

A cable designed by CQR to meet all aspects of the European Construction Product Regulation (CPR) EN50575.

This cable has been independently tested and certified by an accredited test facility and has been awarded a CPR Euro classification.


CQR offer the Installer, Specifier and End User a quality cabling solution and piece of mind that the product will perform to specification in the event of a fire.

DOP Certificates available online for download



Construction

- LSZH Class D_{ca} material used for cores & jacket
- 100% Untinned copper cores
- Screened
- Solid Strand 1 x 0.76mm



EUROCLASS RATING FOR CQR CLASS C CABLES			
	Smoke Production	Flame Droplets	Acidity
D_{ca}	s1a	d0	a1

Designed & Manufactured in the UK

Product codes

Code	Mtrs
CABS2HF/WH/SO/100/D	100mtrs
CABS4HF/WH/SO/100/D	100mtrs

Technical data

Core:	1 x Ø 0.76
Resistance:	38 Ohms/Km
Resistance:	21
Conductor area:	0.454mm ²
Max voltage:	50 volts
Sheathing:	LSZH
Core insulation:	LSZH
Operating temp:	-10°C to +70°C
Drain wire:	Soft tinned copper 1 x Ø 0.5mm
Screen:	Alu/Polyester Foil

rev. 4-10/2020



www.cqr.co.uk

info@cqr.co.uk

Sales: +(0)151 606 1000 Tech: +(0)151 606 6311

CQR Security Ltd, 125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

- 30 Years experience of alarm cable manufacturing in the United Kingdom
- Wide range of cable types; standard, screened, low smoke & fume, twisted pair and power & data
- User friendly, easy to strip & pliable in use

