
## **Data sheet**

## DA314-2K2-6K8

FL2

FL3





**Resistor pack** 

R1 \_\_\_\_\_ FL1

Connections		
FL1	Fly lead – Black 100mm	
FL2	Fly lead – 📕 Red 100mm	
FL3	Fly lead – 📕 Blue 100mm	
R1	2Κ2Ω	
R2	6K8Ω	
Environmental		
Operating temperature	-10°C to +40°C	
Storage temperature	-20°C to +50°C	
Operating relative humidity	Maximum 95% non-condensing	
Dimensions*		
Width	10mm	
Height	18mm	
Depth	4mm	
Weight	< 0.005Kg	
Enclosure material	Polyolefil heat shrunk insulation	
Finish	Black	
Other		
Estimated mean time before failure (MTBF)	50,000 hours	
CE Approved	Yes	
		*(+/- 2mm)

**R2** 

The enclosed information is believed to be correct. Information may change 'without notice' due to product improvement. Users should ensure that the product is suitable for their use. E&OE. Registered Proprietor: Benham (General Engineers) Ltd (No. 1181752) Registered at 3 Galliford Road Industrial Estate, Heybridge, Maldon, Essex CM9 4XD, UK. Directors: R.A.Scott, K.E.Horwood, T.J.Scott, N.J.Scott. VAT Reg. GB 28276273 Tel:+44(0)1621 856 850 Fax:+44(0)1621 856 162 sales@dantech.uk.com