

# DC148R4.7

Industrial surface mount contact, high security grade 3, white with 4k7 EOL resistor

## Requirements for grade 3 magnetic contacts


---

The grade 3 magnetic contacts are high security contacts which do meet the following requirements: preciseness of opening distance, magnet polarisation, strength of the magnet

## Model with built in EOL resistors available

---

Though built in EOL resistors are not mandatory according to EN50131-2.6 requirements, Interlogix offers a model with built in EOL resistors for a quick installation (see how to Order information)



## Details

---

- EN 50131-2-6 Grade 3 and VDS certified
- 2m cable
- covers to be clipped
- Tamper protected
- Built in 4k7 EOL resistor

# DC148R4.7

Industrial surface mount contact, high security grade 3, white with 4k7 EOL resistor

## Technical specifications

---

### General

Application type	Surface Mount
Contact type	1 pin NC contact
Connectivity	LIYY 4 x 0.14 mm Cu tin-plated; Suitable for LSA IDC method of termination

---

### Wired/wireless

Wired-wireless	Wired
----------------	-------

---

### Electrical

Voltage	max 100V DC
Contact power	max 6W or 6 VA
Switching current	max 500mA
Contact resistance	max 0.15 Ohm

---

### Physical

Physical dimensions	54 x 13 x 12.5 mm
Colour	White
Dimensions contact / sensor	8 x 8 x 40 mm
Operating gap	12 mm

---

### Environmental

Operating temperature	-25 to 70°C
IP rating	IP67

---

### Standards & regulation

EN50131 grade	Grade 3
---------------	---------

---

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

29 April 2019 - 13:51