

DS215AHDA-2

LED Monitor

DS215AHDA-2

| | |
|-------------------------------|-------------------------------------|
| Panel Type | 21.5" Led Monitor |
| Case Type | Plastic |
| Maximum Resolution | 1920 (H) x 1080 (V) |
| MTBF | 50,000 hrs |
| Active Display Area | 476.26 x 267.61 (HxV) |
| Pixel Pitch | 0.24825 x 0.24825 (HxV) mm |
| Bezel Thickness | Left / Right / Top 2mm, Bottom 16mm |
| Contrast Ratio | 1000 : 1 |
| Brightness | 250 cd / m ² |
| Response Time | 5m.sec (G to G) |
| Viewing Angle | 178 / 178° (H/V) |
| Display Colours | 16.7m |
| Video Synchronisation | Yes |
| PC Compatibility | N/A |
| Aspect Ratio | 16:9 |
| VGA Auto Frequency Correction | N/A |
| Speakers | 0 |
| Sound Demodulation | No |
| Mute | N/A |
| Work Humidity | 5% - 90% |
| Work Temperature | 0 - 40 °C |
| Volume +/- Power On/Off | Yes |



IN / OUT INTERFACE

| | |
|--------------------|--|
| Video Interface | 2 x HD analogue BNC in (CVBS, AHD, CVI, TVI) 2 x HD analogue BNC out (CVBS, AHD, CVI, TVI) HDMI in |
| Audio Interface | No |
| Termination | 75 Ohms |
| Certification | FCC-DOC, CE, ROHS |
| VESA | 100mm x 100mm |
| Stand Type | Desk |
| Colour | Black |
| Button Position | Front, Bottom Right |
| Packing Dimensions | 548mm x 110mm x 370mm |
| Gross Weight | 4.1kg |

POWER

| | |
|-------------------|--------------|
| Power Supply | 220 / 240 AC |
| Power Consumption | 25 Watt |
| Voltage: | 12v DC |
| Power Interface | DC in x 1 |

OSD CONTROLS

Contrast, Brightness, Saturation, Hue,
Language, OSD position, OSD Time, Reset

OSD LANGUAGE

English, French, German, Spanish, Italian,
Dutch, Polish, Russian, Danish

ACCESSORIES

Power Cord, Adapter, Stand, Users Guide,
HDMI Cable

