# solenoid bolt

# Slimline - EB250 & EB250KO

The Alpro EB250 & EB250KO key override bolts allow for both remote access and exit control of most timber and metal doors. It is also suitable for sliding or swing, single or double action operations. It can be fitted in the frame or in the door. With concealed mortise mounting and slimline styling the bolts suit most narrow stile aluminium doors and narrow profile joinery.

# **High Physical Security**

Holding force 1,000kg - Bolt throw 14mm

### **Robust Construction**

All stainless steel bolt of 14mm diameter, linkages and springs. 3mm stainless steel faceplate and strike plates with fully enclosed mechanism.

#### **Versatile Installation**

Designed to provide concealed high security locking on any single or double action, hinged or sliding door in timber or metal for vertical or horizontal mounting.

#### **Slimline Dimensions**

EB250 210mm(L) x 25mm(W) x 43mm(H)
Back box 160mm(L) x 22mm(W) x 40mm(H)
EB250KO 230mm(L) x 25mm(W) x 43mm(H)
Back box 180mm(L) x 22mm(W) x 40mm(H)

## **Faceplates**

Radius

# **Multiple Voltage Input**

Any voltage from 12v DC/24v DC. Complete with built in transient and reverse polarity protection and continuously rated solenoid.

### **Low Current Consumption**

Volts Current - Activate Current - Hold 12v DC 740mA 120mA 24v DC 440mA 70mA

# **Auto Relock Function**

Can be set to 0, 3, 6 or 9 seconds (DIP switch)

#### **Monitoring**

EB250 - Dual monitoring
Door position switch/bolt position switch
EB250KO - Triple monitoring
Door position switch/bolt position switch/key
position switch



## Maintained Key Override (EB250KO only)

Using standard Euro profile cylinder case pierced both sides for operation either side.

# Ordering Information/Specifications



DESCRIPTION	FUNCTION	CODE
12-24vDC Radius Cover Faceplate 12-24vDC Key Override Radius Cover Faceplate	Fail Safe/PTL Fail Secure/PTO	EB-250/PTL EB-250KO/PTO
ACCESSORIES		
Glass mounting bracket for EB250 (frameless door) Glass SMK dress plates (2) for EB250 Short strike plate with square hole for EB250 Surface mounting kit for EB250 (Stainless Steel) Short strike plate with square hole for EB250KO		EB-250/GMB EB-250/SMK-DP EB-250/SHORT EB-250/SMH-KIT EB-250KO/SHORT

# Dimensional drawings shown are for the EB250 Dimensions for EB250KO model are shown in red where different. 12.5 0 25 40 43 47.5 **③** 4 **③** 197.5 (217.5) 210 (230) **③** 47.5 **④** 25 - 12.5 12.5 -20 30.5 (O) 25