



FIRE RAY® 5000

Motorised Infrared Optical Beam Smoke Detector

Features

- Modular Design
- *Easifit* First Fix System
- Integral LASER
- *Auto-Align* Automatic Beam Alignment
- *Auto-Optimise* Building Movement and Contamination Compensation
- Low Level System Controller
- 2-wire interface from System Controller to Detector
- Worldwide Approvals including EN54:12 and UL268

The **FIRE RAY® 5000** is the first of a new family of auto aligning infrared optical beam smoke detector products and accessories. This innovative system has been designed from the ground up to include pioneering technology that fully addresses the needs of the installer and user, both now and in the future.

With its industry leading optics, the **FIRE RAY® 5000** is ideally suited for the protection of large areas where the use of traditional detection technologies would prove to be too difficult and/or costly to install. The **FIRE RAY® 5000** combines an infrared transmitter and receiver in the same discrete unit and operates by projecting a well-defined beam to a reflective prism, which returns the beam to the receiver for analysis. Smoke in the beam path causes a drop in power, which, if below a pre-determined level, results in an alarm signal.

Getting the system operational is simplified by a number of groundbreaking features that combine to make the **FIRE RAY® 5000** the quickest and easiest detector of its type to install.

A full range of installation accessories are available including the Universal Bracket, which allows a greater degree of flexibility during installation.

Once the detector head is connected, using the *Easifit* First Fix system, an integral LASER can be activated. This allows the reflective prism to be sighted quickly and with confidence. Once the LASER has been used to coarsely align the beam, *Auto-Align* takes over and automatically steers the beam into the optimum position.

The system can be fully customised, according to local conditions; alarm thresholds (sensitivity) and time to Alarm/Fault can be set from the low level System Controller.

The system is fully compliant with the requirements of RoHS & WEEE and is supplied with a 5-year warranty as standard.

data

Unit 9 Hunting Gate
Hitchin
Hertfordshire SG4 0TJ England
T. +44 (0)1462 444740
F. +44 (0)1462 444789
E. sales@ffeuk.com
W. www.ffeuk.com

FIRERAY® 5000

Motorised Infrared Optical Beam
Smoke Detector



Installation Recommendations

Please refer to our installation guides for mounting and wiring instructions. The installation of the **FIRERAY® 5000** infrared optical beam smoke detector should be undertaken in accordance with recognised national or international standards and codes of practice.

Technical Specification

Parameter	Min.	Typ.	Max.	Unit
Operating Voltage (to System Controller)	14	-	28	VDC
Operating Current - low current mode	8	10	12	mA
Operating Current - high current mode	48	50	52	mA
Response Threshold/ Sensitivity (Default 35%)	0.45	-	3.98	dB
	10	-	60	%
Delay to Alarm – user settable (Default 10 sec)	2	-	30	sec
Delay to Fault – user settable (Default 10 sec)	2	-	30	sec
Operating distance (separation) *	8	-	100	m
Maximum angular misalignment of Detector from optical axis	-	-	±0.3	Deg
Maximum angular misalignment of Reflector from optical axis	-	-	±5	Deg
Maximum angular alignment	-	-	±3.5	Deg
Optical wavelength		850		nm
Fault level/ Rapid obscuration ($\Delta \leq 2$ sec)	-	-	87	%
Operating temperature	-10	-	+55	Deg C
Storage temperature	-40	-	+85	Deg C
Relative humidity (non condensing)	-	-	93	%
IP rating		54		-
Contact Voltage - Fire & Fault relays (DPCO)	0.1	-	36	VDC
Contact Current - Fire & Fault relays (DPCO)	0.1	-	100	mA
Cable length – System Controller to Detector (2 core screened fire resistant)	-	-	100	m
Cable gauge	24	-	14	AWG
	0.5	-	1.5	mm
Housing flammability rating	UL94 V0			
CPD Reference	0832-CPD-0565			
UL File	S3417			

All figures are quoted for 25 deg C

* 4 Reflectors required for > 50 m operation

Approximate Dimensions:

Description	Width	Height	Depth	Weight
	mm	mm	mm	kg
System Controller, including base:	200	235	71	0.9
Detector, including 'easy fit' base:	134	135	134	0.5
Universal Bracket:	134	134	70.5	0.2
Reflector:	105	100	9.5	0.07

Dimensions

