

## UV-IR FLAME DETECTOR



### Ordering

FIK-UV-IR-AS11	Detector with M25 conduit openings
FIK-UV-IR-AS21	Detector with 3/4" NPT conduit openings
FIK-TMO-S01 <sup>1</sup>	Tilt Mount, Stainless Steel (shown above)
FIK-TMA-S01 <sup>1,2</sup>	Adapter, Universal Overhead Mount
FIK-USB/RS485 <sup>1,3</sup>	RS-485 to USB Converter Kit
FIK-Weather Cover <sup>1,4</sup>	Weather Cover, Stainless Steel

<sup>1</sup> Ordered separately

<sup>2</sup> Used for mounting a detector to other manufacturers mounting bracket. Installs on top of the detector.

<sup>3</sup> Converts detector RS-485 communication network to USB for connection to a computer port.

<sup>4</sup> Used only in very hot or very cold environments.

### Introduction

The UV-IR flame detector provides ultra-fast response, high performance and reliable detection of a large variety of fires including hydrocarbon fires (visible and non- visible), as well as Hydrogen fires. The detector addresses slow growing fires as well as fast eruptions of fire using improved UV-IR technology. The detector operates in all weather and light conditions.

### Key Benefits

- High immunity to false alarm
- Hydrogen and Hydrocarbons flame detection.
- Ultra-fast detection mode detection within 5 milliseconds for fireballs or explosions
- High sensitivity – up to 100 ft. (30m) for a 1 ft<sup>2</sup> (0.1m<sup>2</sup>) n-heptane pan fire
- Data/Event logger – alarms, faults and other relevant events are logged to non-volatile memory
- Built-in-Test (BIT) – Automatic and manual internal self-test of window cleanliness and the overall operation of the detector
- Window heater to avoid condensation and icing
- Tilt mounting bracket can be connected either above or below the detector
- UV and IR warning levels – 0-20mA – Current output warning when elevated UV or IR radiation is detected

This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

## Immunity to False Alarm

False Alarm Source	Modulated		Unmodulated	
	Distance ft. (m)	Response	Distance ft. (m)	Response
Sunlight, Direct, Reflected		No Alarm		No Alarm
Incandescent frosted glass light, 300W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Fluorescent, 70W (3x23.3W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric arc	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Arc welding	10.0 (3.0)	No Alarm	10.0 (3.0)	No Alarm
Radiation heater, 2000W	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Halogen lamp (1000W)	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Halogen lamp (500W) non-shielded	7.0 (2.0)	No Alarm	7.0 (2.0)	No Alarm
Mercury vapor lamp 160Wx3	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Exhausts	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Projector LED	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Solenoid bell	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Soldering iron	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm
Electric Drill	2.0 (0.6)	No Alarm	2.0 (0.6)	No Alarm

## Response Characteristics

Fuel	Size	Sensitivity	Distance ft. (m)	Average Response Time (s)
N-Heptane	1 x 1 ft.	Extreme	98 (30)	2.0
N-Heptane	1 x 1 ft.	High	75 (23)	1.7
N-Heptane	1 x 1 ft.	Medium	49 (15)	1.0
N-Heptane	1 x 1 ft.	Low	16 (5)	1.0
Gasoline	2 x 2 ft.	Extreme	197 (60)	3.3
Gasoline	1 x 1 ft.	Extreme	98 (30)	1.8
Gasoline	1 x 1 ft.	Medium	49 (15)	1.3
Methane	32-in Plume	Extreme	59 (18)	1.4
Methane	32-in Plume	Medium	30 (9)	0.9
LPG	32-in Plume	Extreme	75 (23)	1.2
LPG	32-in Plume	High	56 (17)	1.6
LPG	32-in Plume	Medium	33 (10)	1.2
LPG	32-in Plume	Low	13 (4)	1.2
Diesel	1 x 1 ft.	Extreme	75 (23)	2.6
Diesel	1 x 1 ft.	Medium	36 (11)	1.2
JP5	2 x 2 ft.	Extreme	75 (23)	3.3
JP5	1 x 1 ft.	High	56 (17)	1.8
JP5	1 x 1 ft.	Medium	36 (11)	1.2
JP5	1 x 1 ft.	Low	16 (5)	1.2
Kerosene	1 x 1 ft.	Extreme	75 (23)	1.8
Kerosene	1 x 1 ft.	Medium	36 (11)	0.9
Methanol	1 x 1 ft.	Extreme	52 (16)	0.8
Methanol	1 x 1 ft.	High	43 (13)	3.2
Methanol	1 x 1 ft.	Medium	30 (9)	1.3
Methanol	1 x 1 ft.	Low	10 (3)	2.7
Ethanol	1 x 1 ft.	Extreme	62 (19)	4.1
Ethanol	1 x 1 ft.	Medium	31 (9.5)	2.9
Isopropanol	1 x 1 ft.	Extreme	75 (23)	2.2
Isopropanol	1 x 1 ft.	Medium	36 (11)	0.8
Polypropylene	1 x 1 ft.	Extreme	49 (15)	1.4
Polypropylene	1 x 1 ft.	Medium	23 (7)	0.9
Paper	1 x 1 ft.	Extreme	33 (10)	1.2
Paper	1 x 1 ft.	Medium	23 (7)	1.0
H <sub>2</sub>	32-in Plume	Extreme	66 (20)	6.4
H <sub>2</sub>	32-in Plume	Medium	33 (10)	1.0

This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.

FIRE DETECTION	<b>Detection time and distance</b>	5ms for fast burst of explosion 1s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 0-50 ft. (0-15m) <2s for 1 ft <sup>2</sup> (0.1m <sup>2</sup> ) n-heptane pan fire at 50-100 ft. (15-30m)
	<b>Field of view (IR detection)</b>	90° Horizontal, 80° Vertical
	<b>Time Delay</b>	0-30 seconds
	<b>Built in Test</b>	Automatic or Manual
ELECTRICAL SPECIFICATIONS	<b>Operating Voltage</b>	24 VDC nominal (18-32 VDC)
	<b>Current Consumption</b>	Standby: 120mA 180mA all systems in operation (including window heater)
	<b>Conduit Entries</b>	2X conduit entries ¾" 14NPT or M25x1.5
	<b>Wiring</b>	12-20AWG (2.5-0.35mm <sup>2</sup> )
OUTPUTS	<b>Relays</b>	Volt-free contacts rated 2A at 30 VDC Alarm – normally open Fault – normally closed
	<b>0-20mA (stepped) current output</b>	3 wire and 4 wire configurations (sink and source)
	<b>Indication</b>	Tri-color LED
	<b>Modbus</b>	RTU compatible on RS-485
MECHANICAL SPECIFICATIONS	<b>Size</b>	5.51 x 3.54 x 3.54" (140 x 90 x 90 mm)
	<b>Weight</b>	Detector (stainless steel 316): 6.6 lbs. (3.0 kg) Tilt mount (stainless steel 316): 3.3 lbs. (1.5 kg)
ENVIRONMENTAL SPECIFICATIONS	<b>Temperature Range</b>	Operating: -67°F to +167°F (-55°C to +75°C) Option: -67°F to +185°F (-55°C to +85°C) Storage: -67°F to +185°F (-55°C to +85°C)
	<b>Humidity</b>	Up to 99% (RH), non-condensing
	<b>Ingress Protection</b>	IP66 & 68 (2m, 24hr); NEMA 4X & 6P
APPROVALS*	<b>Explosion proof</b>	ATEX: II 2 G D  Ex db IIC T5 Gb or Ex db eb IIC T5 Gb and Ex tb IIIC T95°C Db -55°C<Ta<75°C Ex db IIC T4 Gb or Ex db eb IIC T4 Gb and Ex tb IIIC T105°C Db -55°C<Ta<85°C  IECEX Ex db IIC T5 Gb -50°C≤Ta≤75°C Ex db IIC T4 Gb -50°C≤Ta≤85°C  FM & FMC Class I, Div. 1, Groups B, C & D: T4 Class I, Zone 1, AEx/Ex db IIC T4 Gb T4 -50°C≤Ta≤85°C T5 -50°C≤Ta≤75°C
	<b>Performance</b>	ANSI FM 3260  EN 54-10
ACCESSORIES	<b>Weather shield</b>	
	<b>Adapters</b> for connecting different mounts	
WARRANTY	<b>5 Years</b>	

\*All products designed and tested to relevant approval standards.

This document is only intended to be a guideline and is not applicable to all situations. Information is subject to Fike's full disclaimer at <http://www.fike.com/disclaimer>.