Data sheet



Sensor-switched outdoor light

GL 80 LED iHF

Silver EAN 4007841055486



Function description

Elevated, classy light for gardens and the like. The ideal sensor-switched bollard light for use anywhere around the building. As a single light or interconnected path light for installation along driveways. Easy to adjust and interconnect by app and Bluetooth. 63.25 cm in height, its base is made of durable aluminium and finished in anthracite or silver. Light enclosure in UV-resistant plastic. Concealed iHF sensor (160°) with a reach of up to 5 m. With soft-light start, nigh light function (10-50%) and manual override (3000 K).

Technical specifications

Dimensions (L x W x H)	132 x 110 x 632,5 mm	
Mains power supply	220 – 240 V , 50 / 60 Hz	
Sensor Technology	iHF (intelligent high-frequency technology)	
Output	9,5 W	
Interconnection	Yes	
Luminous flux	632 lm	
Colour temperature	3000 K	
Colour Rendering Index CRI	80-89	
With lamp	Yes, STEINEL LED system	
Lamp	LED cannot be replaced	
LED life expectancy (max. °C)	50000 h	
Base	without	
LED cooling system		
EED booling system	Passive Thermo Control	
With motion detector	Passive Thermo Control Yes	
With motion detector	Yes	
With motion detector Detection angle	Yes 160 °	

Data sheet



Sensor-switched outdoor light

		0	
GL	80	LED	iHF

Silver

EAN 4007841055486

Technical specifications

Mechanical scalability	No
Reach, detail	Detection zone adjustable on 3 axes
Reach, radial	r = 5 m (35 m²)
Reach, tangential	r = 5 m (35 m²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 sec – 60 min
Basic light level function	Yes
Basic light level function time	10-30 min, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK03
IP rating	IP44
Protection class (without earth terminal)	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
With remote control	Yes
Version	Silver
PU1, EAN	4007841055486

Data sheet



Sensor-switched outdoor light

GL 80 LED iHF

Silver EAN 4007841055486

Mood image

