

Technical Specification



Product Code: HDMIX120KVM

Description: HDMI 1080p KVM Extender 120m



Receiver

General Information

Supported Resolutions 480p@60Hz, 480i@60Hz,

576p@50Hz, 576i@50Hz,

720p@50/60Hz, 1080p@50/60Hz,

1080i@50/60Hz

Audio Stereo

Transmission

Transmission Connection RJ45

Effective Distance 80 Meters (Cat5)

100 Meters (Cat5e) 120 Meters (Cat6)

Inputs

HDMI 1

USB KVM Connections 1; From control device

Construction

Material Aluminium Alloy

Video Standards

HDMI Compliance 1.3 HDCP Compliance 1.2

Outputs

HDMI 1 Passthrough

Power

5VDC@ 1A

 $\textbf{Consumption} \quad < 3.5 W$

Environment

Ingress Protection IP20
Operating Temperature 0°C to 40°C

Dimensions 140mm x 89mm x 25mm

Features

Extends HDMI signal up to 120 meters via network cable

Connect a DVR or NVR HDMI output to a monitor

Includes KVM function for mouse control connection to enable access to

DVR or NVR menu

Supports up to 1080p Full High Definition Resolution

CAT5(80 meters), CAT5e(100meters), CAT6(120 meters) recommended

Multiple applications for HDMI devices (Audio Supported)

Transmitter

Power Supply 5VDC1A
Power Consumption <3.5W

HDMI Outputs 1
USB KVM connections 2

Dimensions 140mm x 89mm x 25mm

User Manual 2 x 5V1A PSU

> FHDVC4FBBWF 2MP 4mm Fixed Lens Bullet Camera in Black FHDVC4FDWF 2MP 4mm Fixed Lens Dome Camera in White FHDVC4FDBWF 2MP 4mm Fixed Lens Dome Camera in Black

Unit 7 Target Park, Shawbank Road,
Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com

