



HDUBKITP

1 Channel Power & HD Video UTP Transceiver

The HDUBKITP is a passive (non-amplified) Video Balun kit that allows transmission of real-time AHD, HD-CVI, HD-TVI and CVBS Video and Low Voltage Power over CAT5 / CAT6 / UTP Cable. The product features a female DC plug to connect a power adapter as well as a male DC plug to output power from the camera.



HDUBKITP

Key Features

- Transmits Video and Provides the Camera with Power at the same time.
- 4 In 1 Design (AHD, HD-CVI, HD-TVI, CVBS)
- Over-Current Protection
- Suitable for Concentrated Wiring
- Surge Protection
- DC Loop Output
- Kit comprises of 2 Units on for Each End.

Technical Specification

Model Number	HDUBKITP
Channels	1 Channel (Video & Camera Power)
Transmission Distance	0-300m
Video Connector	BNC-M
UTP Connector	RJ45
Compatibility	AHD, HD-CVI, HD,TVI, CVBS Video
Signal Transmitting Band	0-70 MHz
Interference Rejection	>60dB
Power Connector	2.1 / 5.5mm DC Jack
Surge	2KV (Differential Mode), 4KV (Common Mode) Per: IEC61000-4-5
Voltage Range	DC12V~36V
Maximum Current	1A
ESD	Contact Discharge: 6KV, Air Discharge: 8KV Per: IEC61000-4-2
Temperature Conditions	Operating: 0-55°C, Storage: -40~85°C, Humidity: 0-95%(Non-Condensing)
Dimensions	65 x 36 x 23 mm (Cable Length: 60mm)

Genie CCTV reserves the right to change specifications without notice. Please contact your representative to confirm current specifications.

Typical System Application

