



IB911

Access Control

Active Cotag keyring tag

The IB911 is a factory-encoded active tag that includes a lithium battery which enables it to provide hands-free functionality when it is used together with Cotag hands-free readers. For example, the combination of the IB911 tag and the HF500-Cotag reader results in a reading range of approximately 89 cm. The reading range when the IB911 is used in combination with Cotag proximity readers varies from approximately 6 to 17 cm. IB911 tags are particularly useful in environments where some cardholders are disabled or often have their hands full (i.e. a hospital or warehouse)

One of the major advantages of Cotag technology is that active and passive cards can be mixed in the same system to provide ultimate convenience and cost-efficiency.

Note: The card number is printed on the back of the card.

Quantity in order: 1

Technical data

IB911

Dimensions (W x H x D)	31.24 x 49.89 x 9.7 mm
------------------------	------------------------

Details for ordering

Type	Part no	Designation
IB911	S24246-D5204-A1	Active Cotag keyring tag

Issued by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
D-76181 Karlsruhe
www.buildingtechnologies.siemens.com

© 2009 Copyright by
Siemens Building Technologies
Fire & Security Products GmbH & Co. oHG
Data and design subject to change without notice.
Supply subject to availability.

Document no. **A6V10081565**
Edition 06.2009