

'INTER' Range



ELMDENE

Security & Fire
Products

'InterSounder'

Single output for alarm mode

'InterDual'

Hi/Lo output for keypad and
alarm modes

'InterStrobe'

Hi/Lo output with Strobe

Benefits:

Attractively designed range of Internal
Sounders

Desirable appearance for domestic
applications

'Engineer Friendly' for easy installation
and maintenance

Ideal for multiple residential
installations

Low current consumption

Individual Cover logo can be supplied

Features:

- WHITE POLYCARBONATE COVER
- ATTRACTIVELY STYLED FOR RESIDENTIAL PROPERTIES
- SIREN AND STROBE ON 'INTERSTROBE'
- FRONT AND BACK TAMPER
- ADJUSTABLE VOLUME CONTROL ON SELECTED MODELS
- SAB AVAILABLE ON ALL MODELS
- 20 MINUTE CUT-OFF TIMER (SELECTABLE)
- ENGINEER MODE FOR SILENT START-UP
- SCREEN PRINTING AVAILABLE

**Internal Sounders
you can rely on**

www.elmdene.co.uk



INTRUDER



'INTER' Range

Specifications

Model	Part No.	Sound Mode	Sound Output (dB @ 1m)	Current (mA)
InterSounder	INT400	Alarm only	120	180
(with SAB)	INT400S			
InterDual	INT600	Hi/Lo	120 (Alarm)	260 (Alarm)
(with SAB)	INT600S	(Keypad and Alarm)	80 (Keypad)	80 (Keypad)
InterStrobe	INT500	Hi/Lo	120 (Alarm)	260 (Alarm)
(with SAB)	INT500S	(Keypad and Alarm)	80 (Keypad)	80 (Keypad)

Dimensions

160mm x 110mm x 40mm

Materials:

Cover

Polycarbonate (3mm)

Siren:

Input Voltage (all models)

12V dc Nominal

Operating Voltage (all models)

13.8V Nominal

Current

See table above

Sound Output

See table above

Strobe (on INT500 only):

Input Voltage

12V dc Nominal


Flash Rate

1 per second Nominal

Full SAB option (on all models)

6V NiMH (150mAh)

ELMDENE INTERNATIONAL LIMITED
 Rodney Road, Fratton, Portsmouth PO4 8SS United Kingdom
 Tel: +44 (0)23 9273 9412 Fax: +44 (0)23 9281 1631
 e-mail: sales@elmdene.co.uk



ELMDENE

Security & Fire
 Products

www.elmdene.co.uk