## Data sheet



Motion detector

## **IS 140-2 Z-Wave**

white EAN 4007841029814



#### **Function description**

The classic detector, now with even more class. Infrared motion detector IS 140-2 Z-Wave, can be integrated into the Smart Friends system or any other Z-Wave network, for indoors and out, ideal for targeted detection close to the building, 140° angle of coverage, reach up to 14 m, selectable time and twilight threshold, sensor turns through 180° and tilts through 90° for exact adjustment of the detection zone.

#### **Technical specifications**

Туре	Motion detectors
Dimensions (L x W x H)	95 x 86 x 70 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2 m
Detection angle	140 °
Angle of aperture	40 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 3 m (11 m²)
Reach, tangential	r = 14 m (239 m²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 sec – 35 min

## Data sheet



Motion detector

# IS 140-2 Z-Wave

white EAN 4007841029814

#### **Technical specifications**

Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	6 pcs.
With bus coupling	No
IP rating	IP54
Material	Plastic
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
PU1, EAN	4007841029814