



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



Video door entry kit consisting of n° 1 Mini hands-free monitor art. 6741W, 1 branch terminal art. 1214/2C, n° 1 termination terminal art. 1216, n° 1 power supply art. 1210, n° 1 pushbutton panel Switch series with 1 button art. IX0101 with relative flush-mounting box art. IX9150 and n° 1 colour audio/video unit. Simplebus2 system.



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT

PRODUCTS IN THE KIT



IX9150 FLUSH-MOUNTED BOX FOR FRONT PLATE W/ 1-2-3-4 BUTT.

Flush-mounted box for entrance panels art. IX0101, IX0102, IX0103 and IX0104 with 1-2-3-4 buttons. Dimensions: 124x236.7x56 mm.

MAIN FEATURES	
Height (mm)	236.7
Width (mm)	124
Depth (mm)	56
GENERAL DATA	
Type of finishing materials	Steel zinc coated
Product color	Steel
COMPATIBILITY	
Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
MOUNTING/INSTALLATION	
Flush-mounted	Yes



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



IX0101 SWITCH FRONT PLATE WITH 1 BUTTON

Front plate for Switch entrance panel in 2.5 mm thick brushed AISI 316 stainless steel. Adapter art. 1250U (supplied) offers the option of using the audio or audio/video module - not supplied - depending on the type of wiring applied (Simplebus digital 2-wire or ViP). Complete with 1 pre-fitted, pre-wired button. White LED nameplate backlighting. Nameplate replacement from the front. Protection rating IK08. To be finished with flush-mounted box or surface-mounted casing (not supplied). Dimensions (L x H x P): 150 x 262.7 x 2.5 mm.

GENERAL DATA	
Type	Monoblock
Height (mm)	262.7
Width (mm)	150
Depth (mm)	2.5
Product color	Steel
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.1621, Art.1621VC, Art.1622, Art.1622VC, Art.4680C, Art.4681
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT

AUDIO FEATURES

Technologies implemented	Echo canceling
--------------------------	----------------

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	White

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP54
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	III



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



6741W SB2 MINI HANDSFREE WI-FI DOOR ENTRY MONITOR

Mini series hands-free Wi-Fi door entry monitor for Simplebus 2 system. When used in conjunction with the Comelit app (available to download free of charge from the Google and Apple stores) and/or the Alexa/Echo Show/Google Assistant voice assistants, it can be used to answer calls directly from your smartphone/tablet/voice assistant device, both locally and remotely. It can be used to enable the “Face recognition” function, to automatically - once a person has been recognised - send a lock-release command (enabled by default), trigger an actuator to control a light or additional opening and receive notification when a known individual makes a call. It can be used to operate new wi-fi home automation devices in the WiFree range by Comelit. It is also possible to control devices with different protocols, thereby integrating any third-party home automation system for the control of gates, outdoor lights, scenario activation, etc. Replacing an old door entry monitor to benefit from all the advantages offered by Wi-Fi technology is no longer problematic: Mini Wi-Fi is actually compatible with all types of Comelit Simplebus 2 video entry phone system and does not require any additional masonry work. Supplied with mounting backplate and riser distribution terminal art. 1214/2C.

GENERAL DATA	
Height (mm)	160
Width (mm)	115
Depth (mm)	22
Product color	White RAL9003
Type of finishing materials	ABS
Product weight (g)	400
Wall-mounted	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT

COMPATIBLE SYSTEMS

Simplebus 2 audio/video kit with power supply art. 1209	Yes
---	-----

DISPLAY

Display size (")	4.3
------------------	-----

Aspect Ratio	16:9
--------------	------

Resolution (pixels)	480x272
---------------------	---------

OSD menu	Yes
----------	-----

Type of display	LCD
-----------------	-----

AUDIO FEATURES

Type	Hands-free
------	------------

Microphone	6mm (Ø), Omnidirectional
------------	--------------------------

Loudspeaker	36mm (Ø), 40 Ohm, 1W
-------------	----------------------

Technologies implemented	Full-Duplex
--------------------------	-------------

ELECTRICAL CHARACTERISTICS

Type of power supply	Power supply from video door entry bus
----------------------	--

Supply voltage	22÷34 VDC (Bus)
----------------	-----------------

Absorption in stand-by (W)	0.1
----------------------------	-----

Stand-by absorption in kit mode (W)	1.9
-------------------------------------	-----

Maximum absorption (W)	8.1
------------------------	-----

HARDWARE FEATURES

Type of buttons	Capacitive
-----------------	------------

Service buttons	Lock-release, Answer, Silent (Privacy), Menu, Messages, Door open
-----------------	---

No. of programmable buttons for additional functions	4
--	---

Clamps	L L CFP1 CFP2
--------	---------------

Removable terminals	Yes
---------------------	-----



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT

HARDWARE FEATURES

Number of inputs (n°)	1
-----------------------	---

SETTINGS

Loudspeaker volume	Yes
--------------------	-----

Ringtone volume	Yes
-----------------	-----

Screen brightness control	Yes
---------------------------	-----

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
--------------------------	---

Encryption and authentication method supported	OPEN WPA-PSK networks, TKIP WPA2-PSK, AES WEP 64 bits (5-digit ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26 hexadecimal codes)
--	--

IP address assignment	DHCP
-----------------------	------

IoT connection to Comelit Cloud	Yes
---------------------------------	-----

Firmware update via Comelit Cloud	Yes
-----------------------------------	-----

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection rating	IP30
----------------------	------

Operating temperature (°C)	5 ÷ 40
----------------------------	--------

Operating humidity (RH max) (%)	25 ÷ 75
---------------------------------	---------

Environmental class	I
---------------------	---

CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)
-------------------	--

GENERAL FEATURES

Door opening on call (Doctor)	Yes
-------------------------------	-----

Door opener	Yes
-------------	-----

Self Activation	Yes
-----------------	-----

CPS call	Yes
----------	-----



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT

GENERAL FEATURES

Selective intercom call	Yes
Intercom calls	Yes
Actuator control	Yes
Comaptibility with Video Entry Comelit App	Yes
Hands-free function	Yes
Multiple address	Yes
Outside door call input	Yes
Integration with voice assistants	Yes
Sending alarm calls	Yes
Video memory	Yes
Silent mode (Privacy)	Yes
Face recognition	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Yes
Customisable ringtone	Yes
Date/time display	Yes



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



1210 SIMPLEBUS2 POWER SUPPLY UNIT

2-wire power supply unit required to power the external unit (terminals L1 - L1) and the support column (terminals L2 - L2). Equipped with 1 terminal for line termination art 1216. Input voltage 110-240Vac. Compatible with audio/video unit art. 4681 and 1621VC and audio unit art. 1621. Dimensions: 106x89x62mm (6 DIN modules).

MAIN FEATURES	
Supply voltage	110÷240
Max. current delivered (A)	1.2
Applicable to DIN rail	Yes
Number of DIN modules (n°)	6
GENERAL DATA	
Height (mm)	108
Width (mm)	90
Depth (mm)	62
Operating temperature (°C)	-10 ÷ 40
COMPATIBILITY	
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
AUDIO/VIDEO FEATURES	
Audio/video system	Yes
ELECTRICAL SPECIFICATIONS	
Maximum current absorption (mA)	800
Maximum power delivered (W)	40



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



1216 SIMPLEBUS2 LINE TERMINATION TERMINAL

Line termination terminal. To be mounted at the end of the riser, according to the indications given in the technical documentation, to optimise distribution of the signals.

GENERAL FEATURES	
Input connector	Terminal block
CE certifications	EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
MAIN FEATURES	
Operating temperature (°C)	-5 ÷ 40
Operating humidity (RH max) (%)	25 ÷ 95
COMPATIBILITY	
Simplebus 2 audio/video system	Yes



KVS2011

SB2 SWITCH AND MINI HANDSFREE WI-FI KIT



1214/2C VIDEO FILTER FOR S2 SYSTEM

Line branch terminal for colour monitors. The terminal must be connected on the riser to be branched towards brackets or telephones.

MAIN FEATURES

Height (mm)	25
Width (mm)	32
Depth (mm)	25.5
Operating temperature (°C)	-10 ÷ 30

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Simplebus 2 audio system	Yes

AUDIO/VIDEO FEATURES

Audio system	Yes
Audio/video system	Yes