

SPECIFICATION SHEET

DIMMABLE LED DRIVERS

The range of LED Tridonic Drivers are suitable for use on LED sources from 25 - 100W. The Installation is screw and tool-free.

Applications

- Commercial Kitchens
- Leisure Centres
- Educational Providers

Additional Information

- 1-100% Dimming control
- 3 Dimming options: DALI, DSI and Switch Dim/ Push Dim



Material:	Polycarbonate
Life Expectancy:	100,000 Hours
Working Temperature:	-25°C - 65°C (LEDDRIVER36D: -25°C - 50°C)

Code	Wattage	Dimensions (L x W x D mm)
LEDDRIVER36D	25W-45W	215 x 70 x 30
LEDDRIVER100D	45W-100W	235 x 100 x 30

8W LED DRIVER



The LED Drivers are available in various wattages, the 8W version is compatible with our LED cabinet lighting.

Applications

- Residential
- Retail



Material:	Polycarbonate
Life Expectancy:	30,000 Hours
Working Temperature:	-2°C - 50°C

Dimensions (L x W x D mm):	118 x 44 x 20
---------------------------------------	---------------

Code	Wattage
LEDPS-8W	8W

15W LED DIMMABLE DRIVER

The compact LED Driver, dimmable via leading-edge and trailing-edge phase cut dimmers.

Applications

- Commercial Kitchens
- Leisure Centres
- Educational Providers



Material:	Polycarbonate
Life Expectancy:	60,000 Hours
Working Temperature:	-23°C - 50°C

Dimensions (L x W x D mm):	102 x 51 x 30
---------------------------------------	---------------

Code	Wattage
LEDDRIVER15PHC	15W

36W LED DRIVER

The LED Driver is suitable for use with LED Panels (up to 36W).

Applications

- Commercial Kitchens
- Leisure Centres
- Educational Providers



Material:	Polycarbonate
Life Expectancy:	50,000 Hours
Working Temperature:	-30°C - 50°C

Dimensions (L x W x D mm):	115 x 41 x 28
---------------------------------------	---------------

Code	Wattage
BLP36-DRIVER	36W