

NFW-SDT/DL3 Kit

FRESCape lite is a unique, highly cost effective and environmentally friendly emergency lighting solution, combining the existing FIREscape luminaire and exit sign ranges with a uniquely designed 'step-down' transformer, allowing them to be mains-powered.

The lighting units and exit signs can be fitted at any location where a connection to the lighting circuit can be made. By combining the existing lighting units with the transformer, a spacer, a mounting base and the integral back-up battery, the resulting self-contained, self-diagnosing unit provides an instant and easy-to-install lighting solution, fully compliant with the requirements of BS5266.





Step-Down Transformer

The step-down transformer is used when converting the existing FIREscape luminaires and exit signs into mains-driven, stand-alone lighting units.

- Combines with spacer and mounting base
- Features flying leads to connect to mounting base and mains lighting circuit (includes cable crimps)
- Low profile only 4mm



Intelligent Open Space Down Light

An LED-based, open space down light featuring one high-powered LED with a specially engineered dual surface free-form optic. The unit's body contains the electronics and the stand-by battery and features a bi-coloured LED indicating charge/fault status (green for charging, red for fault).

- Complies with BS5266 for open areas
- LED technology
- Status LED
- For ceilings up to 3 meters
- Non-maintained by default
- Luminaires awarded BSI Kitemark™ 🕏









NFW-SDT/DL3 Kit





Spacer

The spacer combines with the step-down transformer and mounting base when converting the FIREscape luminaires and exit signs into mains-driven, stand-alone units.

- Combines with step down transformer and mounting base
- Colour matches FIREscape products
- ▶ Low profile only 16mm



Mounting Base

The mounting base, combines with the step-down transformer and spacer when converting the FIREscape luminaires and exit signs into mains driven stand-alone units.

- Electronics Free
- Stainless steel contacts
- ▶ Low profile only 8 mm



Battery

An intelligent rechargeable Lithium/Polymer back-up battery for use with both luminaires and exit signs within the FIREscape range.

- 450 mAh/7.4 V
- For use with luminaires and exit signs
- Incorporates deep discharge protection circuitry
- Provides the BS5266 minimum 3 hour back-up time

Non-Maintained	Open Area to 0.5 Lux	
Mounting Height (m)	Spacing to Wall	Spacing Between
2.50	3.25	7.37
3.00	3.04	8.37

^{*}For other mounting heights see our website.



