

### **Datasheet**

# **ELECTRO-MAGNETIC LOCKS/ P300EVO - P600EVO - Magnetic Architectural LED Monitored Handle**

#### **Product description**

Magnetic handles are becoming increasingly popular with sites that require strong holding forces and more aesthetic solutions. The entire range from CDVI is ideal for locations where a stronger lock is essential; such as schools, halls of residence and other public buildings.

P300EVO & P600EVO are 600mm handles incorporating 1 x 300kg or 2 x 300kg monitored magnets and can be used externally.

The handles are monitored and indicate the status of the door (open or closed) with LEDs.

#### **Key features**

- Surface mount architectural handle
- Retrofit or new build
- Vertical or horizontal installation
- Custom RAL colours (optional)
- Visual feedback with LEDs







Certification



DEEE



RoHS Certification



-20°C to 70°C



*TP42* 



IK10





#### **Product Specifications**

**Holding force:** 

P300EVO: 1 x 300kg P600EVO: 2 x 300kg

**Mounting:** Vertical or horizontal **Fitting:** Retrofit or new build

**Optional:** 

UBK25: Bracket for glass door installations

REOMA60: Cable tray and spacer kit

PRP800: Mimic handle section

Direct push button input

Flame retardant spring terminals

## **Electrical Specifications** (per magnet)

Free voltage: 10Vdc to 60Vdc Operating voltage: 12/24/48Vdc

Current consumotion: @12Vdc = 480mA,

@24Vdc = 240mA, @48Vdc = 120mA

